



**SPC BENCHMARK 1C™
FULL DISCLOSURE REPORT**

**SEAGATE TECHNOLOGY LLC
SEAGATE ST600MX0004 600GB 15K
6GBPS SAS 2.5" SSHD HYBRID**

SPC-1C V1.5

**Submitted for Review: October 29 2013
Submission Identifier: C00018**

First Edition – October 2013

THE INFORMATION CONTAINED IN THIS DOCUMENT IS DISTRIBUTED ON AN AS IS BASIS WITHOUT ANY WARRANTY EITHER EXPRESS OR IMPLIED. The use of this information or the implementation of any of these techniques is the customer's responsibility and depends on the customer's ability to evaluate and integrate them into the customer's operational environment. While each item has been reviewed by Seagate Technology LLC for accuracy in a specific situation, there is no guarantee that the same or similar results will be obtained elsewhere. Customers attempting to adapt these techniques to their own environment do so at their own risk.

This publication was produced in the United States. Seagate Technology LLC may not offer the products, services, or features discussed in this document in other countries, and the information is subject to change with notice. Consult your local Seagate Technology LLC representative for information on products and services available in your area.

© Copyright Seagate Technology LLC 2013. All rights reserved.

Permission is hereby granted to reproduce this document in whole or in part, provided the copyright notice as printed above is set forth in full text on the title page of each item reproduced.

Trademarks

SPC Benchmark-1C, SPC-1C, SPC-1C IOPS and SPC-1C LRT are trademarks of the Storage Performance Council. Seagate, Seagate Technology, the Wave logo and Seagate Savvio are registered trademarks of Seagate Technology LLC in the United States and other countries. Savvio is either a trademark or registered trademark of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other brands, trademarks, and product names are the property of their respective owners.

Table of Contents

Audit Certification	vii
Audit Certification (<i>cont.</i>)	viii
Letter of Good Faith	ix
Executive Summary	10
Test Sponsor and Contact Information	10
Revision Information and Key Dates	10
Tested Storage Product (TSP) Description	11
Summary of Results	12
Storage Capacities, Relationships, and Utilization	13
Response Time – Throughput Curve	16
Response Time – Throughput Data	16
Priced Storage Configuration Pricing	17
Differences between the Tested Storage Configuration (TSC) and Priced Storage Configuration	17
Benchmark Configuration/Tested Storage Configuration Diagram	18
Host System and Tested Storage Configuration Components	18
Configuration Information	19
Benchmark Configuration (BC)/Tested Storage Configuration (TSC) Diagram	19
Host System(s) and Tested Storage Configuration (TSC) Table of Components	19
Customer Tunable Parameters and Options	19
Tested Storage Configuration (TSC) Description	20
SPC-1C Workload Generator Storage Configuration	20
ASU Pre-Fill	20
SPC-1C Data Repository	21
Storage Capacities and Relationships	21
SPC-1C Storage Capacities	21
SPC-1C Storage Hierarchy Ratios	22
SPC-1C Storage Capacity Charts.....	22
Storage Capacity Utilization	24
Logical Volume Capacity and ASU Mapping	25
SPC-1C Benchmark Execution Results	26
SPC-1C Tests, Test Phases, and Test Runs	26
“Ramp-Up” Test Runs	27
Primary Metrics Test – Sustainability Test Phase	27
SPC-1C Workload Generator Input Parameters.....	28

Sustainability Test Results File	28
Sustainability – Data Rate Distribution Data (MB/second)	28
Sustainability – Data Rate Distribution Graph	28
Sustainability – I/O Request Throughput Distribution Data	29
Sustainability – I/O Request Throughput Distribution Graph	29
Sustainability – Average Response Time (ms) Distribution Data	30
Sustainability – Average Response Time (ms) Distribution Graph	30
Sustainability – Response Time Frequency Distribution Data	31
Sustainability – Response Time Frequency Distribution Graph	31
Sustainability – Measured Intensity Multiplier and Coefficient of Variation.....	32
Primary Metrics Test – IOPS Test Phase.....	33
SPC-1C Workload Generator Input Parameters.....	33
IOPS Test Results File.....	33
IOPS Test Run – I/O Request Throughput Distribution Data	34
IOPS Test Run – I/O Request Throughput Distribution Graph.....	34
IOPS Test Run – Average Response Time (ms) Distribution Data	35
IOPS Test Run – Average Response Time (ms) Distribution Graph	35
IOPS Test Run –Response Time Frequency Distribution Data	36
IOPS Test Run –Response Time Frequency Distribution Graph.....	36
IOPS Test Run – I/O Request Information.....	37
IOPS Test Run – Measured Intensity Multiplier and Coefficient of Variation.....	37
Primary Metrics Test – Response Time Ramp Test Phase	38
SPC-1C Workload Generator Input Parameters.....	38
Response Time Ramp Test Results File.....	38
Response Time Ramp Distribution (IOPS) Data.....	39
Response Time Ramp Distribution (IOPS) Data (<i>continued</i>)	40
Response Time Ramp Distribution (IOPS) Graph	40
SPC-1C LRT™ Average Response Time (ms) Distribution Data	41
SPC-1C LRT™ Average Response Time (ms) Distribution Graph.....	41
SPC-1C LRT™ (10%) – Measured Intensity Multiplier and Coefficient of Variation....	42
Repeatability Test	43
SPC-1C Workload Generator Input Parameters.....	43
Repeatability Test Results File	44
Repeatability 1 LRT – I/O Request Throughput Distribution Data.....	45
Repeatability 1 LRT – I/O Request Throughput Distribution Graph	46
Repeatability 1 LRT –Average Response Time (ms) Distribution Data	47
Repeatability 1 LRT –Average Response Time (ms) Distribution Graph.....	48
Repeatability 1 IOPS – I/O Request Throughput Distribution Data	49
Repeatability 1 IOPS – I/O Request Throughput Distribution Graph.....	50

Repeatability 1 IOPS –Average Response Time (ms) Distribution Data	51
Repeatability 1 IOPS –Average Response Time (ms) Distribution Graph	52
Repeatability 2 LRT – I/O Request Throughput Distribution Data.....	53
Repeatability 2 LRT – I/O Request Throughput Distribution Graph	54
Repeatability 2 LRT –Average Response Time (ms) Distribution Data	55
Repeatability 2 LRT –Average Response Time (ms) Distribution Graph.....	56
Repeatability 2 IOPS – I/O Request Throughput Distribution Data	57
Repeatability 2 IOPS – I/O Request Throughput Distribution Graph.....	58
Repeatability 2 IOPS –Average Response Time (ms) Distribution Data.....	59
Repeatability 2 IOPS –Average Response Time (ms) Distribution Graph	60
Repeatability 1 (LRT) Measured Intensity Multiplier and Coefficient of Variation	61
Repeatability 1 (IOPS) Measured Intensity Multiplier and Coefficient of Variation	61
Repeatability 2 (LRT) Measured Intensity Multiplier and Coefficient of Variation	61
Repeatability 2 (IOPS) Measured Intensity Multiplier and Coefficient of Variation	62
Data Persistence Test.....	63
SPC-1C Workload Generator Input Parameters.....	63
Data Persistence Test Results File	63
Data Persistence Test Results.....	64
Priced Storage Configuration Availability Date.....	65
Pricing Information.....	65
Tested Storage Configuration (TSC) and Priced Storage Configuration Differences.....	65
Anomalies or Irregularities	65
Appendix A: SPC-1C Glossary	66
“Decimal” (<i>powers of ten</i>) Measurement Units.....	66
“Binary” (<i>powers of two</i>) Measurement Units.....	66
SPC-1C Data Repository Definitions	66
SPC-1C Data Protection Levels.....	67
SPC-1C Test Execution Definitions.....	67
I/O Completion Types	69
SPC-1C Test Run Components	69
Appendix B: Customer Tunable Parameters and Options.....	70
Appendix C: Tested Storage Configuration (TSC) Creation	71
Create RAID-5 Array.....	71
RB50.cmd.....	71
Create SPC-1C Logical Volumes	71
diskmkhdd.txt	72

Change Parameters	72
TuneParmBase.cmd	72
Appendix D: SPC-1C Workload Generator Storage Commands and Parameters	73
ASU Pre-Fill	73
Primary Metrics Test, Repeatability and Persistence Tests.....	73
Appendix E: SPC-1C Workload Generator Input Parameters	74
Primary Metrics Test, Repeatability Test and Persistence Test Run 1	74
Persistence Test Run 2.....	74
Appendix F: Third-Party Quotations.....	75
Storage Enclosure	75
LSI MegaRAID Controller	76
SAS Cables	77

AUDIT CERTIFICATION



Craig Parris
Seagate Technology LLC
1280 Disc Drive
Shakopee, MN 55379

October 23, 2013

The SPC Benchmark 1C™ results listed below for the Seagate ST600MC0004 600GB 15K 6Gbps SAS 2.5" SSHD Hybrid were produced in compliance with the SPC Benchmark 1C™ V1.5 Audit requirements.

SPC Benchmark 1C™ V1.5 Reported Data	
Tested Storage Product (TSP):	
Seagate ST600MC0004 600GB 15K 6Gbps SAS 2.5" SSHD Hybrid	
Metric	Reported Result
SPC-1C Submission Identifier	C00018
SPC-1C IOPS™	7,197.38
Total ASU Capacity	10,792.364 GB
Data Protection Level	Protected 1 (RAID-5)
Total Price – Priced Storage Configuration	\$24,602.00
Currency Used	U.S. Dollars
Target Country for availability, sales and support	USA

The following SPC Benchmark 1C™ Audit requirements were reviewed and found compliant with V1.5 of the SPC Benchmark 1C™ specification:

- A Letter of Good Faith, signed by a senior executive.
- The following Data Repository storage items were verified by physical inspection and information supplied by Seagate Technology LLC:
 - ✓ Physical Storage Capacity and requirements.
 - ✓ Configured Storage Capacity and requirements.
 - ✓ Addressable Storage Capacity and requirements.
 - ✓ Capacity of each Logical Volume and requirements.
 - ✓ Capacity of each Application Storage Unit (ASU) and requirements.
- The entire Configured Storage Capacity was filled with random data, using an auditor approved tool, prior to the execution of the SPC-1C Tests.

Storage Performance Council
643 Bair Island Road, Suite 103
Redwood City, CA 94062
AuditService@storageperformance.org
650.556.9384

AUDIT CERTIFICATION (CONT.)

Seagate ST600MC0004 600GB 15K 6Gbps SAS 2.5" SSHD Hybrid
SPC-1C Audit Certification

Page 2


- An appropriate diagram of the Benchmark Configuration (BC)/Tested Storage Configuration (TSC).
- Physical verification of the components to match the above diagram.
- Listings and commands to configure the Benchmark Configuration/Tested Storage Configuration, including customer tunable parameters that were changed from default values.
- SPC-1C Workload Generator commands and parameters used for the audited SPC-1C Test Runs.
- The following Host System requirements were verified by physical inspection and information supplied by Seagate Technology LLC:
 - ✓ The type of Host System including the number of processors and main memory.
 - ✓ The presence and version number of the SPC-1C Workload Generator on the Host System.
 - ✓ The TSC boundary within the Host System.
- The execution of each Test, Test Phase, and Test Run was observed and found compliant with all of the requirements and constraints of Clauses 4 and 5 of the SPC-1C Benchmark Specification.
- The Test Results Files and resultant Summary Results Files for each of following were authentic, accurate, and compliant with all of the requirements and constraints of Clauses 4, 5 and 6 of the SPC-1C Benchmark Specification:
 - ✓ Data Persistence Test
 - ✓ Sustainability Test Phase
 - ✓ IOPS Test Phase
 - ✓ Response Time Ramp Test Phase
 - ✓ Repeatability Test
- There were no differences between the Tested Storage Configuration (TSC) used for the benchmark and Priced Storage Configuration.
- The submitted pricing information met all of the requirements and constraints of Clause 9 of the SPC-1C Benchmark Specification.
- The Full Disclosure Report (FDR) met all of the requirements in Clause 10 of the SPC-1C Benchmark Specification.
- IBM Corporation granted Seagate Technology LLC permission to submit this successfully audited SPC measurement for the Seagate ST600MC0004 600GB 15K 6Gbps SAS 2.5" SSHD Hybrid to become a new SPC-1C Result.
- This successfully audited SPC measurement is not subject to an SPC Confidential Review.

Audit Notes:

There were no audit notes or exceptions.

Respectfully,

Walter E. Baker



SPC Auditor

Storage Performance Council
643 Bair Island Road, Suite 103
Redwood City, CA 94062
AuditService@storageperformance.org
650.556.9384

LETTER OF GOOD FAITH



Seagate Technology
1280 Disc Drive
Shakopee, MN 55379

Date: *October 4th 2013*

From: John Morris

To: *Walter Baker*

Subject: SPC-1C Letter of Good Faith for Seagate ST600MX0004 600GB 15K 6Gbps SAS 2.5" SSHD Hybrid.

Seagate Technology is the SPC-1C Test Sponsor for the above listed product. To the best of our knowledge and belief, the required SPC-1C benchmark results and materials we have submitted for that product are complete, accurate, and in full compliance with *V1.5* of the SPC-1C benchmark specification.

In addition, we have reported any items in the Benchmark Configuration and execution of the benchmark necessary to reproduce the reported results even if the items are not explicitly required to be disclosed by the above SPC-1C benchmark specification.

Signed:

Date:

 _____ *10/14/2013*

John Morris
Vice President, Enterprise Product Development

Seagate Technology
1280 Disc Drive
Shakopee, MN 55379

EXECUTIVE SUMMARY

Test Sponsor and Contact Information

Test Sponsor and Contact Information	
Test Sponsor Primary Contact	Seagate Technology LLC – http://www.seagate.com Craig Parris – craig.parris@seagate.com 1280 Disc Drive Shakopee, MN 55379 Phone: (952) 402-2418
Test Sponsor Alternate Contact	Seagate Technology LLC – http://www.seagate.com Barbara Craig – barbara.j.craig@seagate.com 1280 Disc Drive Shakopee, MN 55379 Phone: (952) 402-2804
Auditor	Storage Performance Council – http://www.storageperformance.org Walter E. Baker – AuditService@StoragePerformance.org 643 Bair Island Road, Suite 103 Redwood City, CA 94063 Phone: (650) 556-9384 FAX: (650) 556-9385

Revision Information and Key Dates

Revision Information and Key Dates	
SPC-1C Specification revision number	V1.5
SPC-1C Workload Generator revision number	V1.2.0
Date Results were first used publicly	October 29 2013
Date the FDR was submitted to the SPC	October 29 2013
Date the Priced Storage Configuration is available for shipment to customers	January 15, 2014
Date the TSC completed audit certification	October 23, 2013

Tested Storage Product (TSP) Description

The amount of information that is gathered and stored by businesses continues to grow exponentially. In addition to the demand for increased storage, there are increasing requirements to quickly and effectively store and access data. Today, conventional hard disk drives and solid-state storage technology are utilized to achieve specific objectives within the data center. Conventional hard disk drives continue to be the most common storage media offering high density and basic performance in a cost-effective solution. Solid-state storage solutions enable businesses to achieve optimal input/output (IO) through variable read/write capabilities for performance intensive applications and workloads.

Seagate is now offering a new technology: hybrid drives. These drives combine a cache of NAND flash and conventional media to accelerate hard disk drive performance - enabling higher IO performance while leveraging the capacity and cost of spinning media for primary storage.

Seagate is introducing 6 Gbps SAS 2.5-inch hybrid drives - namely Enterprise Turbo SSHD - the first generation of 15K-RPM hybrid drives from Seagate. Ideal for medium businesses or the distributed large enterprise, the Enterprise Turbo SSHD provides cost-effective performance and density in a small form factor hard disk drive.

In addition to the solid-state-based cache, these new drive offerings provide optimal 6 Gbps hot-swap SAS capability for your high-performance and high-availability server and storage environments. Hard drive functionality and 6 Gbps SAS performance of these new hybrid drives are enabled when used with traditional Enterprise servers and internal RAID controllers

Summary of Results

SPC-1C Reported Data	
Tested Storage Product (TSP) Name: Seagate ST600MX0004 600GB 15K 6Gbps SAS 2.5" SSHD Hybrid	
Metric	Reported Result
SPC-1C Submission Identifier	C00018
SPC-1C IOPS™	7,197.38
Total ASU Capacity	10,792.364 GB
Data Protection Level	Protected 1 (RAID-5)
Total Price	\$24,602.00
Pricing Currency	U.S. Dollars
Target Country for availability, sales and support	USA

SPC-1C Submission Identifier is the unique identifier assigned to this specific SPC-1C Result.

SPC-1C IOPS™ represents the maximum I/O Request Throughput at the 100% load point.

Total ASU (Application Storage Unit) Capacity represents the total storage capacity available to be read and written in the course of executing the SPC-1C benchmark.

A **Data Protection Level** of **Protected 1** using **RAID-5** by distributing check data corresponding to user data across multiple disk in the form of bit-by-bite parity.

***Protected 1:** The single point of failure of any **storage device** in the configuration will not result in permanent loss of access to or integrity of the SPC-1C Data Repository.*


Total Price includes the cost of the Priced Storage Configuration plus three years of hardware maintenance and software support as detailed on page 17.



Pricing Currency is formal name for the currency used in calculating the **Total Price**. That currency may be the local currency of the **Target Country** or the currency of a difference country (*non-local currency*).


The **Target Country** is the country in which the Priced Storage Configuration is available for sale and in which the required hardware maintenance and software support is provided either directly from the Test Sponsor or indirectly via a third-party supplier.

Storage Capacities, Relationships, and Utilization

The following four charts and table document the various storage capacities, used in this benchmark, and their relationships, as well as the storage utilization values required to be reported.







The Tested Storage Configuration (TSC) must be configured so that there is either no more than 1 GB of Unused Storage (100% utilization) or that the sum of Total ASU Capacity and storage required for data protection equals 50% (+-1 GiB) of the Physical Storage Capacity.


The TSC met the “100% utilization” requirement since it did not include any Unused Storage.

Detailed information for the various storage capacities and utilizations is available on pages 21-22.

Response Time – Throughput Curve

The Response Time-Throughput Curve illustrates the Average Response Time (milliseconds) and I/O Request Throughput at 100%, 95%, 90%, 80%, 50%, and 10% of the workload level used to generate the SPC-1C IOPS™ metric.

The Average Response Time measured at any of the above load points cannot exceed 30 milliseconds or the benchmark measurement is invalid.



Response Time – Throughput Data

	10% Load	50% Load	80% Load	90% Load	95% Load	100% Load
I/O Request Throughput	719.23	3,599.79	5,758.04	6,480.52	6,839.46	7,197.38
Average Response Time (ms):						
All ASUs	0.79	1.17	1.62	2.74	5.13	9.43
ASU-1	1.03	1.53	2.12	3.53	6.28	10.95
ASU-2	1.24	1.80	2.47	4.28	8.46	15.88
ASU-3	0.08	0.13	0.18	0.38	1.25	3.37
Reads	1.89	2.79	3.85	6.53	11.95	21.20
Writes	0.07	0.12	0.17	0.27	0.69	1.76

Priced Storage Configuration Pricing


Description	Part Numbers	Qty	Price	Extended Price
600GB SAS 2.5" SSHD	ST600MX0004	24	\$812.00	\$19,488.00
6Gb SAS RAID Controller	LSI SAS 9265-8i	1	\$700.00	\$700.00
Storage Enclosure JBOD	DNS-1640D	1	\$4,295.00	\$4,295.00
SAS 2.0 1M Cable	MiniSAS	2	\$59.50	\$119.00
			Total	\$24,602.00

Differences between the Tested Storage Configuration (TSC) and Priced Storage Configuration

There were no differences between the TSC and Priced Storage Configuration.

Benchmark Configuration/Tested Storage Configuration Diagram

**24 – Seagate ST600MX0004 600GB
15K 6Gbps SAS 2.5” HDDs**



Host System and Tested Storage Configuration Components

Host System	Tested Storage Configuration (TSC)
“Generic” Windows 2008 Server ASUS P6T6 WS Revolution motherboard 1 – Intel® Xeon® Processor X5570 4 Cores, 2.93 GHz, 8 MB Intel® Smart Cache	1 – LSI MegaRAID 6Gb/s SAS 9265-8i RAID controller with 1 GB cache
12 GB main memory	1 – PCIe 2.0 x8 front-end connection
Windows Server 2008 R2	2 – 6Gb SAS backend connections (<i>failover mode</i>) (4 lanes/connection, 2 connections used)
PCIe 2.0	24 – Seagate ST600MX0004 600GB 15K 6Gbps SAS 2.5” SSHD Hybrid HDDs
	1 – Dataon DNS-1640 (JBOD) storage enclosure (2U 24-bay 2.5” 6Gb/s SAS)
	2 –SAS 2.0 1m cables

In each of the following sections of this document, the appropriate Full Disclosure Report requirement, from the SPC-1C benchmark specification, is stated in italics followed by the information to fulfill the stated requirement.

CONFIGURATION INFORMATION

Benchmark Configuration (BC)/Tested Storage Configuration (TSC) Diagram

Clause 10.4.5.11

The Executive Summary will contain a one page BC/TSC diagram that illustrates all major components of the BC/TSC.

The Benchmark Configuration (BC)/Tested Storage Configuration (TSC) is illustrated on page [18](#) ([Benchmark Configuration/Tested Storage Configuration Diagram](#)).

Host System(s) and Tested Storage Configuration (TSC) Table of Components

Clause 10.4.5.12

The Executive Summary will contain a table that lists the major components of each Host System and the Tested Storage Configuration (TSC).

The Host System(s) and TSC table of components may be found on page [18](#) ([Host System and Tested Storage Configuration Components](#)).

Customer Tunable Parameters and Options

Clause 10.4.6.1

All Benchmark Configuration (BC) components with customer tunable parameters and options that have been altered from their default values must be listed in the Full Disclosure Report (FDR). The FDR entry for each of those components must include both the name of the component and the altered value of the parameter or option. If the parameter name is not self-explanatory to a knowledgeable practitioner, a brief description of the parameter's use must also be included in the FDR entry.

[Appendix B: Customer Tunable Parameters and Options](#) on page [70](#) contains the customer tunable parameters and options that have been altered from their default values for this benchmark.

Tested Storage Configuration (TSC) Description

Clause 10.4.6.2

The Full Disclosure Report must include sufficient information to recreate the logical representation of the Tested Storage Configuration (TSC). In addition to customer tunable parameters and options (Clause 10.4.6.1), that information must include, at a minimum:

- A diagram and/or description of the following:
 - All physical components that comprise the TSC. Those components are also illustrated in the BC Configuration Diagram in Clause 10.4.5.10.
 - The logical representation of the TSC, configured from the above components that will be presented to the SPC-1C Workload Generator.
- Listings of scripts used to create the logical representation of the TSC.
- If scripts were not used, a description of the process used with sufficient detail to recreate the logical representation of the TSC.

[Appendix C: Tested Storage Configuration \(TSC\) Creation](#) on page [71](#) contains the detailed information that describes how to create and configure the logical TSC.

SPC-1C Workload Generator Storage Configuration

Clause 10.4.6.3

The Full Disclosure Report will include all SPC-1C Workload Generator storage configuration commands and parameters used in the SPC-1C benchmark measurements.

The SPC-1C Workload Generator storage configuration commands and parameters for this measurement appear in [Appendix D: SPC-1C Workload Generator Storage Commands and Parameters](#) on page [73](#).

ASU Pre-Fill

Clause 6.3.3

Each of the three SPC-1C ASUs (ASU-1, ASU-2 and ASU-3) is required to be completely filled with specified content prior to the execution of audited SPC-1C Tests. The content is required to consist of random data pattern such as that produced by an SPC recommended tool.

The configuration file used to complete the required ASU pre-fill appears in [Appendix D: SPC-1C Workload Generator Storage Commands and Parameters](#) on page [73](#).

SPC-1C DATA REPOSITORY

This portion of the Full Disclosure Report presents the detailed information that fully documents the various SPC-1C storage capacities and mappings used in the Tested Storage Configuration. [SPC-1C Data Repository Definitions](#) on page [66](#) contains definitions of terms specific to the SPC-1C Data Repository.

Storage Capacities and Relationships

Clause 10.4.7.1

Two tables and four charts documenting the storage capacities and relationships of the SPC-1C Storage Hierarchy (Clause 2.1) shall be included in the FDR. ... The capacity value in each chart may be listed as an integer value, for readability, rather than the decimal value listed in [the table below].

SPC-1C Storage Capacities

The Physical Storage Capacity consisted of 14,403.054 GB distributed over 24 disk drives, each with a formatted capacity of 600.127 GB. There was 0.000 GB (0.00%) of Unused Storage within the Physical Storage Capacity. Global Storage Overhead consisted of 13.035 GB (0.09%) of the Physical Storage Capacity. There was 0.000 GB (0.000%) of Unused Storage within the Configured Storage Capacity. The Total ASU Capacity utilized 100.00% of the Addressable Storage Capacity resulting in 0.00 GB (0.00%) of Unused Storage within the Addressable Storage Capacity. The Data Protection (*RAID-5*) capacity was 3,596.503 GB of which 3,596.503 GB was utilized. The total Unused Storage capacity was 0.000 GB.


Note: The configured Storage Devices may include additional storage capacity reserved for system overhead, which is not accessible for application use. That storage capacity may not be included in the value presented for Physical Storage Capacity.



SPC-1C Storage Capacities		
Storage Hierarchy Component	Units	Capacity
Total ASU Capacity	Gigabytes (GB)	10,792.364
Addressable Storage Capacity	Gigabytes (GB)	10,792.364
Configured Storage Capacity	Gigabytes (GB)	14,388.886
Physical Storage Capacity	Gigabytes (GB)	14,403.054
Data Protection (<i>RAID-5</i>)	Gigabytes (GB)	3,596.503
Required Storage	Gigabytes (GB)	1.153
Global Storage Overhead	Gigabytes (GB)	13.035
Total Unused Storage	Gigabytes (GB)	0.000


SPC-1C Storage Hierarchy Ratios

	Addressable Storage Capacity	Configured Storage Capacity	Physical Storage Capacity
Total ASU Capacity	100.00%	75.01%	74.93%
Required for Data Protection (RAID-5)		25.00%	24.97%
Addressable Storage Capacity		75.01%	74.93%
Required Storage		0.01%	0.01%
Configured Storage Capacity			99.90%
Global Storage Overhead			0.09%
Unused Storage:			
Addressable	0.00%		
Configured		0.00%	
Physical			0.00%

SPC-1C Storage Capacity Charts







Storage Capacity Utilization

Clause 2.6.8

The Total ASU Capacity must be configured in one of the following relationships to the Physical Storage Capacity.

Clause 2.6.8.1

100%: The Tested Storage Configuration must be configured so there is 1 GiB or less of total Unused Storage

Clause 2.6.8.2

50%: Total ASU Capacity must be configured so that the sum of Total ASU Capacity and capacity required for data protection is 50% of the Physical Storage Capacity within a tolerance of ± 1 GiB or 0.5% of the Physical Storage Capacity, whichever is greater.

The TSC met the “100% utilization” requirement since it did not include any Unused Storage.

Logical Volume Capacity and ASU Mapping

Clause 10.4.7.2

A table illustrating the capacity of each ASU and the mapping of Logical Volumes to ASUs shall be provided in the FDR. ... Logical Volumes shall be sequenced in the table from top to bottom per its position in the contiguous address space of each ASU. The capacity of each Logical Volume shall be stated. ... In conjunction with this table, the Test Sponsor shall provide a complete description of the type of data protection (see Clause 2.7) used on each Logical Volume.

Logical Volume Capacity and Mapping		
ASU-1 (4,856.564 GB)	ASU-2 (4,856.564 GB)	ASU-3 (1,079.236 GB)
1 Logical Volume 4,856.564 GB per Logical Volume (4,856.564 GB used per Logical Volume)	1 Logical Volume 4,856.564 GB per Logical Volume (4,856.564 GB used per Logical Volume)	1 Logical Volume 1,079.236 GB per Logical Volume (1,079.236 GB used per Logical Volume)

The Data Protection Level used for all Logical Volumes was [Protected 1](#) using **RAID-5** as described on page [12](#). See “ASU Configuration” in the [IOPS Test Results File](#) for more detailed configuration information.

SPC-1C BENCHMARK EXECUTION RESULTS

This portion of the Full Disclosure Report documents the results of the various SPC-1C Tests, Test Phases, and Test Runs. An [SPC-1C glossary](#) on page 66 contains definitions of terms specific to the SPC-1C Tests, Test Phases, and Test Runs.

Clause 6.4.2

The Tests must be executed in the following sequence: Primary Metrics, Repeatability, and Data Persistence. That required sequence must be uninterrupted from the start of Primary Metrics to the completion of Persistence Test Run 1.

Uninterrupted means the Benchmark Configuration shall not be power cycled, restarted, disturbed, altered, or adjusted during the selected Test sequence. If the selected Test sequence is interrupted, the SPC-1C measurement is invalid. This does not apply to the interruption caused by the Host System/TSC power cycle between Persistence Test Run 1 and Persistence Test Run 2.

SPC-1C Tests, Test Phases, and Test Runs

The SPC-1C benchmark consists of the following Tests, Test Phases, and Test Runs:

- **Primary Metrics Test**
 - Sustainability Test Phase and Test Run
 - IOPS Test Phase and Test Run
 - Response Time Ramp Test Phase
 - 95% of IOPS Test Run
 - 90% of IOPS Test Run
 - 80% of IOPS Test Run
 - 50% of IOPS Test Run
 - 10% of IOPS Test Run (LRT)
- **Repeatability Test**
 - Repeatability Test Phase 1
 - 10% of IOPS Test Run (LRT)
 - IOPS Test Run
 - Repeatability Test Phase 2
 - 10% of IOPS Test Run (LRT)
 - IOPS Test Run
- **Data Persistence Test**
 - Data Persistence Test Run 1
 - Data Persistence Test Run 2

Each Test is an atomic unit that must be executed from start to finish before any other Test, Test Phase, or Test Run may be executed.

The results from each Test, Test Phase, and Test Run are listed below along with a more detailed explanation of each component.

“Ramp-Up” Test Runs

Clause 6.3.12

In order to warm-up caches or perform the initial ASU data migration in a multi-tier configuration, a Test Sponsor may perform a series of “Ramp-Up” Test Runs as a substitute for an initial, gradual Ramp-Up.

Clause 6.3.12.4

The “Ramp-Up” Test Runs will immediately precede the Primary Metrics Test as part of the uninterrupted SPC-1C measurement sequence.

Clause 10.4.8.1

If a series of “Ramp-Up” Test Runs were included in the SPC-1C measurement sequence, the FDR shall report the duration (ramp-up and measurement interval), BSU level, SPC-1C IOPS and average response time for each “Ramp-Up” Test Run in an appropriate table.

There were no “Ramp-Up” Test Runs executed in this set of benchmark measurements.

Primary Metrics Test – Sustainability Test Phase

Clause 6.4.3.2

The Sustainability Test Phase has exactly one Test Run and shall demonstrate the maximum sustainable I/O Request Throughput within a continuous one (1) hour Measurement Interval.

Clause 6.4.3.2.6

The computed I/O Request Throughput of the Sustainability Test Run must be no less than 95% of the reported SPC-1C IOPS™ result or the Test Run is invalid.

Clause 6.4.3.2.7

The Average Response Time, as defined in Clause 0, will be computed and reported for the Sustainability Test Run and cannot exceed 30 milliseconds. If the Average Response Time exceeds that 30-millisecond constraint, the Test Run is invalid.

Clause 10.4.8.2

The FDR shall contain the following for the single Test Run in the Sustainability/IOPS Test Phase:

- 1. A Data Rate Distribution graph and data table.*
- 2. I/O Request Throughput Distribution graph and data table.*
- 3. A Response Time Frequency Distribution graph and table.*
- 4. An Average Response Time Distribution graph and table.*
- 5. The human readable Test Run Results File produced by the Workload Generator (may be included in an appendix).*
- 6. A listing or screen image of all input parameters supplied to the Workload Generator (may be included in an appendix).*
- 7. The Measured Intensity Multiplier for each I/O stream.*
- 8. The variability of the Measured Intensity Multiplier, as defined in Clause 5.3.13.3.*

SPC-1C Workload Generator Input Parameters

The SPC-1C Workload Generator input parameters for the Sustainability, IOPS, Response Time Ramp, Repeatability, and Persistence Test Runs are documented in [Appendix E: SPC-1C Workload Generator Input Parameters](#) on Page 74.

Sustainability Test Results File

A link to the test results file generated from the Sustainability Test Run is listed below.


[Sustainability Test Results File](#)

Sustainability – Data Rate Distribution Data (MB/second)

The Sustainability Data Rate table of data is not embedded in this document due to its size. The table is available via the following URL:

[Sustainability Data Rate Table](#)

Sustainability – Data Rate Distribution Graph




Sustainability – I/O Request Throughput Distribution Data

The Sustainability I/O Request Throughput table of data is not embedded in this document due to its size. The table is available via the following URL:

[Sustainability I/O Request Throughput Table](#)

Sustainability – I/O Request Throughput Distribution Graph




Sustainability – Average Response Time (ms) Distribution Data

The Sustainability Average Response Time table of data is not embedded in this document due to its size. The table is available via the following URL:

[Sustainability Average Response Time Table](#)


Sustainability – Average Response Time (ms) Distribution Graph



Sustainability – Response Time Frequency Distribution Data

Response Time (ms)	0-0.25	>0.25-0.5	>0.5-0.75	>0.75-1.0	>1.0-1.25	>1.25-1.5	>1.5-1.75	>1.75-2.0
Read	353,857	4,798,151	5,049,691	4,504,746	5,040,248	4,505,201	3,564,941	3,157,609
Write	112,878,622	5,201,539	1,866,454	264,197	96,743	1,650,279	800,167	162,960
All ASUs	113,232,479	9,999,690	6,916,145	4,768,943	5,136,991	6,155,480	4,365,108	3,320,569
ASU1	49,985,133	6,453,474	5,196,097	4,022,877	4,413,489	4,636,022	3,394,841	2,777,480
ASU2	11,694,343	1,056,017	845,463	619,611	671,245	785,873	578,662	460,745
ASU3	51,553,003	2,490,199	874,585	126,455	52,257	733,585	391,605	82,344
Response Time (ms)	>2.0-2.5	>2.5-3.0	>3.0-3.5	>3.5-4.0	>4.0-4.5	>4.5-5.0	>5.0-6.0	>6.0-7.0
Read	6,051,415	5,089,859	5,335,874	3,943,105	2,827,045	1,725,494	2,529,486	2,001,590
Write	51,373	37,774	34,906	33,426	31,155	29,089	51,652	44,819
All ASUs	6,102,788	5,127,633	5,370,780	3,976,531	2,858,200	1,754,583	2,581,138	2,046,409
ASU1	5,214,900	4,384,488	4,593,315	3,363,523	2,399,492	1,455,619	2,108,351	1,634,910
ASU2	852,525	714,218	750,693	587,190	434,644	276,394	432,313	376,335
ASU3	35,363	28,927	26,772	25,818	24,064	22,570	40,474	35,164
Response Time (ms)	>7.0-8.0	>8.0-9.0	>9.0-10.0	>10.0-15.0	>15.0-20.0	>20.0-25.0	>25.0-30.0	>30.0
Read	1,690,163	1,407,023	1,155,720	3,659,040	1,987,512	1,293,744	947,680	9,164,419
Write	39,600	38,950	42,325	358,796	374,843	268,375	152,756	1,108,587
All ASUs	1,729,763	1,445,973	1,198,045	4,017,836	2,362,355	1,562,119	1,100,436	10,273,006
ASU1	1,349,241	1,132,218	942,704	3,068,168	1,736,740	1,138,506	811,196	7,392,824
ASU2	349,802	284,334	225,407	744,145	420,043	269,715	189,666	1,891,651
ASU3	30,720	29,421	29,934	205,523	205,572	153,898	99,574	988,531

Sustainability – Response Time Frequency Distribution Graph



Sustainability – Measured Intensity Multiplier and Coefficient of Variation

Clause 3.4.3

IM – Intensity Multiplier: The ratio of I/Os for each I/O stream relative to the total I/Os for all I/O streams (ASU1-1 – ASU3-1) as required by the benchmark specification.

Clauses 6.1.10

MIM – Measured Intensity Multiplier: The Measured Intensity Multiplier represents the ratio of measured I/Os for each I/O stream relative to the total I/Os measured for all I/O streams (ASU1-1 – ASU3-1).

Clause 6.3.14.3

COV – Coefficient of Variation: This measure of variation for the Measured Intensity Multiplier cannot exceed 0.5.

	ASU1-1	ASU1-2	ASU1-3	ASU1-4	ASU2-1	ASU2-2	ASU2-3	ASU3-1
IM	0.0350	0.2810	0.0700	0.2100	0.0180	0.0700	0.0350	0.2810
MIM	0.0350	0.2810	0.0700	0.2100	0.0180	0.0700	0.0350	0.2810
COV	0.008	0.003	0.005	0.003	0.011	0.006	0.008	0.002

Primary Metrics Test – IOPS Test Phase

Clause 6.4.3.3

The IOPS Test Phase consists of one Test Run at the 100% load point with a Measurement Interval of five (5) minutes. The IOPS Test Phase immediately follows the Sustainability Test Phase without any interruption or manual intervention.

The IOPS Test Run generates the SPC-1C IOPS™ primary metric, which is computed as the I/O Request Throughput for the Measurement Interval of the IOPS Test Run.

The Average Response Time is computed for the IOPS Test Run and cannot exceed 30 milliseconds. If the Average Response Time exceeds the 30 millisecond constraint, the measurement is invalid.

Clause 10.4.8.3

For the IOPS Test Phase the FDR shall contain:

- 1. I/O Request Throughput Distribution (data and graph).*
- 2. Response Time Frequency Distribution (data and graph).*
- 3. Average Response Time Distribution (data and graph).*
- 4. The human readable SPC-1C Test Run Results File produced by the SPC-1C Workload Generator.*
- 5. A listing of all input parameters supplied to the SPC-1C Workload Generator.*
- 6. The Measured Intensity Multiplier for each I/O Stream.*
- 7. The variability of the Measured Intensity Multiplier, as defined in Clause 6.3.13.3.*
- 8. The total number of I/O Requests completed in the Measurement Interval as well as the number of I/O Requests with a Response Time less than or equal to 30 milliseconds and the number of I/O Requests with a Response Time greater than 30 milliseconds.*

SPC-1C Workload Generator Input Parameters

The SPC-1C Workload Generator input parameters for the Sustainability, IOPS, Response Time Ramp, Repeatability, and Persistence Test Runs are documented in [Appendix E: SPC-1C Workload Generator Input Parameters](#) on Page [74](#).

IOPS Test Results File


A link to the test results file generated from the IOPS Test Run is listed below.

[IOPS Test Results File](#)

IOPS Test Run – I/O Request Throughput Distribution Data

1,440 BSUs	Start	Stop	Interval	Duration
Start-Up/Ramp-Up	18:05:14	18:15:15	0-9	0:10:01
Measurement Interval	18:15:15	18:25:15	10-19	0:10:00
60 second intervals	All ASUs	ASU1	ASU2	ASU3
0	7,195.68	4,277.52	894.30	2,023.87
1	7,199.55	4,293.37	885.30	2,020.88
2	7,205.40	4,284.60	885.45	2,035.35
3	7,207.18	4,298.63	882.98	2,025.57
4	7,180.42	4,279.92	883.25	2,017.25
5	7,182.13	4,279.80	878.27	2,024.07
6	7,188.63	4,292.20	882.05	2,014.38
7	7,206.83	4,291.77	881.95	2,033.12
8	7,189.65	4,286.73	882.97	2,019.95
9	7,213.72	4,305.50	886.65	2,021.57
10	7,202.65	4,280.48	890.37	2,031.80
11	7,195.33	4,288.73	882.28	2,024.32
12	7,189.88	4,288.50	885.83	2,015.55
13	7,193.27	4,295.18	880.08	2,018.00
14	7,195.80	4,289.33	887.93	2,018.53
15	7,219.43	4,300.62	886.48	2,032.33
16	7,200.63	4,289.22	889.38	2,022.03
17	7,203.45	4,290.07	896.37	2,017.02
18	7,195.65	4,283.22	882.92	2,029.52
19	7,177.70	4,280.68	880.92	2,016.10
Average	7,197.38	4,288.60	886.26	2,022.52


IOPS Test Run – I/O Request Throughput Distribution Graph



IOPS Test Run – Average Response Time (ms) Distribution Data

1,440 BSUs Start-Up/Ramp-Up Measurement Interval	Start 18:05:14 18:15:15	Stop 18:15:15 18:25:15	Interval 0-9 10-19	Duration 0:10:01 0:10:00
60 second intervals	All ASUs	ASU1	ASU2	ASU3
0	14.97	16.81	29.07	4.87
1	10.93	12.83	19.17	3.29
2	11.83	13.62	21.04	4.07
3	10.92	12.67	18.83	3.76
4	10.08	11.79	17.25	3.31
5	10.07	11.79	17.20	3.34
6	10.26	11.96	17.55	3.43
7	10.47	12.41	17.10	3.48
8	9.83	11.52	16.49	3.34
9	10.15	11.83	17.01	3.56
10	10.09	11.67	17.21	3.65
11	9.29	10.86	15.81	3.12
12	10.08	11.68	16.58	3.81
13	9.07	10.67	15.33	2.94
14	9.53	11.13	15.91	3.34
15	9.89	11.50	16.57	3.56
16	9.37	10.76	16.36	3.36
17	8.96	10.34	15.02	3.31
18	9.25	10.63	15.55	3.60
19	8.75	10.27	14.44	3.04
Average	9.43	10.95	15.88	3.37

IOPS Test Run – Average Response Time (ms) Distribution Graph




IOPS Test Run –Response Time Frequency Distribution Data

Response Time (ms)	0-0.25	>0.25-0.5	>0.5-0.75	>0.75-1.0	>1.0-1.25	>1.25-1.5	>1.5-1.75	>1.75-2.0
Read	10,211	94,993	100,177	90,393	100,481	90,184	71,931	63,691
Write	2,366,251	108,716	39,315	5,359	1,917	35,004	15,759	3,004
All ASUs	2,376,462	203,709	139,492	95,752	102,398	125,188	87,690	66,695
ASU1	1,050,775	130,253	104,879	81,515	88,836	94,609	69,139	56,575
ASU2	246,421	21,447	16,236	11,692	12,510	15,075	10,844	8,603
ASU3	1,079,266	52,009	18,377	2,545	1,052	15,504	7,707	1,517

Response Time (ms)	>2.0-2.5	>2.5-3.0	>3.0-3.5	>3.5-4.0	>4.0-4.5	>4.5-5.0	>5.0-6.0	>6.0-7.0
Read	121,313	102,538	105,919	78,794	57,167	35,053	50,764	40,090
Write	895	595	584	564	561	509	843	780
All ASUs	122,208	103,133	106,503	79,358	57,728	35,562	51,607	40,870
ASU1	105,692	89,443	92,267	68,091	49,014	29,737	42,220	32,226
ASU2	15,829	13,175	13,741	10,783	8,246	5,398	8,681	7,974
ASU3	687	515	495	484	468	427	706	670

Response Time (ms)	>7.0-8.0	>8.0-9.0	>9.0-10.0	>10.0-15.0	>15.0-20.0	>20.0-25.0	>25.0-30.0	>30.0
Read	33,452	28,500	23,684	78,206	45,152	30,595	22,883	226,798
Write	676	661	609	2,469	2,105	1,787	1,658	24,753
All ASUs	34,128	29,161	24,293	80,675	47,257	32,382	24,541	251,551
ASU1	26,328	22,487	18,789	62,039	36,025	24,495	18,419	179,245
ASU2	7,234	6,121	4,976	16,538	9,435	6,321	4,694	49,760
ASU3	566	553	528	2,098	1,797	1,566	1,428	22,546

IOPS Test Run –Response Time Frequency Distribution Graph



IOPS Test Run – I/O Request Information

I/O Requests Completed in the Measurement Interval	I/O Requests Completed with Response Time = or < 30 ms	I/O Requests Completed with Response Time > 30 ms
4,318,343	4,066,792	251,551

IOPS Test Run – Measured Intensity Multiplier and Coefficient of Variation

Clause 3.4.3

IM – Intensity Multiplier: The ratio of I/Os for each I/O stream relative to the total I/Os for all I/O streams (ASU1-1 – ASU3-1) as required by the benchmark specification.

Clauses 6.1.10

MIM – Measured Intensity Multiplier: The Measured Intensity Multiplier represents the ratio of measured I/Os for each I/O stream relative to the total I/Os measured for all I/O streams (ASU1-1 – ASU3-1).

Clause 6.3.14.3

COV – Coefficient of Variation: This measure of variation for the Measured Intensity Multiplier cannot exceed 0.5.

	ASU1-1	ASU1-2	ASU1-3	ASU1-4	ASU2-1	ASU2-2	ASU2-3	ASU3-1
IM	0.0350	0.2810	0.0700	0.2100	0.0180	0.0700	0.0350	0.2810
MIM	0.0350	0.2809	0.0699	0.2101	0.0180	0.0700	0.0351	0.2810
COV	0.010	0.001	0.006	0.003	0.014	0.006	0.011	0.003

Primary Metrics Test – Response Time Ramp Test Phase

Clause 6.4.3.4

The Response Time Ramp Test Phase consists of five Test Runs, one each at 95%, 90%, 80%, 50%, and 10% of the load point (100%) used to generate the SPC-1C IOPS™ primary metric. Each of the five Test Runs has a Measurement Interval of five (5) minutes. The Response Time Ramp Test Phase immediately follows the IOPS Test Phase without any interruption or manual intervention.

The five Response Time Ramp Test Runs, in conjunction with the IOPS Test Run (100%), demonstrate the relationship between Average Response Time and I/O Request Throughput for the Tested Storage Configuration (TSC) as illustrated in the response time/throughput curve on page 16.

In addition, the Average Response Time measured during the 10% Test Run is the value for the SPC-1C LRT™ metric. That value represents the Average Response Time of a lightly loaded TSC.

Clause 10.4.8.4

The following content shall appear in the FDR for the Response Time Ramp Phase:

- 1. A Response Time Ramp Distribution graph.*
- 2. The human readable Test Run Results File produced by the SPC-1C C Workload Generator for each Test Run within the Response Time Ramp Test Phase.*
- 3. An Average Response Time Distribution graph and table for the 10% BSU Level Test Run (the SPC-1C LRT™ metric).*
- 4. A listing of all input parameters supplied to the SPC-1C Workload Generator.*

SPC-1C Workload Generator Input Parameters

The SPC-1C Workload Generator input parameters for the Sustainability, IOPS, Response Time Ramp, Repeatability, and Persistence Test Runs are documented in [Appendix E: SPC-1C Workload Generator Input Parameters](#) on Page [74](#).

Response Time Ramp Test Results File

A link to each test result file generated from each Response Time Ramp Test Run list listed below.

[95% Load Level](#)

[90% Load Level](#)

[80% Load Level](#)

[50% Load Level](#)

[10% Load Level](#)

Response Time Ramp Distribution (IOPS) Data

The five Test Runs that comprise the Response Time Ramp Phase are executed at 95%, 90%, 80%, 50%, and 10% of the Business Scaling Unit (BSU) load level used to produce the SPC-1C IOPS™ primary metric. The 100% BSU load level is included in the following Response Time Ramp data table and graph for completeness.


100% Load Level - 1,440 BSUs					95% Load Level - 1,368 BSUs				
Start	Stop	Interval	Duration		Start	Stop	Interval	Duration	
18:05:14	18:15:15	0-9	0:10:01		18:25:17	18:35:18	0-9	0:10:01	
Measurement Interval					Measurement Interval				
18:15:15	18:25:15	10-19	0:10:00		18:35:18	18:45:18	10-19	0:10:00	
(60 second intervals)					(60 second intervals)				
All ASUs	ASU-1	ASU-2	ASU-3		All ASUs	ASU-1	ASU-2	ASU-3	
0	7,195.68	4,277.52	894.30	2,023.87	0	6,838.48	4,080.12	837.17	1,921.20
1	7,199.55	4,293.37	885.30	2,020.88	1	6,827.63	4,074.98	839.55	1,913.10
2	7,205.40	4,284.60	885.45	2,035.35	2	6,852.28	4,081.25	842.22	1,928.82
3	7,207.18	4,298.63	882.98	2,025.57	3	6,844.43	4,083.98	837.78	1,922.67
4	7,180.42	4,279.92	883.25	2,017.25	4	6,835.73	4,074.83	841.78	1,919.12
5	7,182.13	4,279.80	878.27	2,024.07	5	6,827.87	4,062.35	840.60	1,924.92
6	7,188.63	4,292.20	882.05	2,014.38	6	6,842.83	4,082.83	840.05	1,919.95
7	7,206.83	4,291.77	881.95	2,033.12	7	6,840.22	4,072.65	843.08	1,924.48
8	7,189.65	4,286.73	882.97	2,019.95	8	6,856.67	4,085.62	839.92	1,931.13
9	7,213.72	4,305.50	886.65	2,021.57	9	6,847.88	4,075.18	843.62	1,929.08
10	7,202.65	4,280.48	890.37	2,031.80	10	6,836.63	4,079.52	839.27	1,917.85
11	7,195.33	4,288.73	882.28	2,024.32	11	6,845.08	4,070.38	845.58	1,929.12
12	7,189.88	4,288.50	885.83	2,015.55	12	6,831.22	4,068.78	839.43	1,923.00
13	7,193.27	4,295.18	880.08	2,018.00	13	6,841.68	4,078.52	839.72	1,923.45
14	7,195.80	4,289.33	887.93	2,018.53	14	6,848.18	4,077.50	847.20	1,923.48
15	7,219.43	4,300.62	886.48	2,032.33	15	6,841.92	4,083.05	841.75	1,917.12
16	7,200.63	4,289.22	889.38	2,022.03	16	6,833.03	4,069.90	836.28	1,926.85
17	7,203.45	4,290.07	896.37	2,017.02	17	6,839.75	4,068.38	849.27	1,922.10
18	7,195.65	4,283.22	882.92	2,029.52	18	6,833.27	4,075.77	843.77	1,913.73
19	7,177.70	4,280.68	880.92	2,016.10	19	6,843.82	4,077.28	839.22	1,927.32
Average	7,197.38	4,288.60	886.26	2,022.52	Average	6,839.46	4,074.91	842.15	1,922.40

90% Load Level - 1,296 BSUs					80% Load Level - 1,152 BSUs				
Start	Stop	Interval	Duration		Start	Stop	Interval	Duration	
18:45:20	18:55:21	0-9	0:10:01		19:05:23	19:15:24	0-9	0:10:01	
Measurement Interval					Measurement Interval				
18:55:21	19:05:21	10-19	0:10:00		19:15:24	19:25:24	10-19	0:10:00	
(60 second intervals)					(60 second intervals)				
All ASUs	ASU-1	ASU-2	ASU-3		All ASUs	ASU-1	ASU-2	ASU-3	
0	6,470.07	3,860.07	797.45	1,812.55	0	5,754.83	3,425.50	701.10	1,628.23
1	6,471.90	3,863.35	788.35	1,820.20	1	5,759.95	3,443.85	700.10	1,616.00
2	6,483.73	3,859.78	801.78	1,822.17	2	5,762.80	3,434.52	706.43	1,621.85
3	6,475.32	3,857.65	797.30	1,820.37	3	5,744.53	3,415.63	705.70	1,623.20
4	6,467.52	3,855.20	793.93	1,818.38	4	5,749.07	3,431.95	707.78	1,609.33
5	6,484.32	3,858.50	801.58	1,824.23	5	5,764.52	3,433.48	706.95	1,624.08
6	6,478.17	3,853.05	798.65	1,826.47	6	5,748.57	3,419.45	707.80	1,621.32
7	6,495.22	3,881.18	797.42	1,816.62	7	5,751.45	3,426.33	705.33	1,619.78
8	6,496.92	3,873.23	799.12	1,824.57	8	5,768.82	3,429.90	707.48	1,631.43
9	6,486.72	3,868.70	795.03	1,822.98	9	5,753.12	3,427.78	709.38	1,615.95
10	6,483.07	3,860.82	798.30	1,823.95	10	5,761.20	3,437.52	707.67	1,616.02
11	6,488.32	3,855.92	799.48	1,832.92	11	5,738.53	3,421.95	707.93	1,608.65
12	6,484.58	3,865.70	800.57	1,818.32	12	5,765.10	3,431.23	714.62	1,619.25
13	6,461.15	3,848.93	795.73	1,816.48	13	5,752.12	3,421.18	706.33	1,624.60
14	6,473.73	3,858.75	796.72	1,818.27	14	5,763.98	3,430.95	709.98	1,623.05
15	6,482.40	3,856.02	797.62	1,828.77	15	5,760.50	3,432.13	710.52	1,617.85
16	6,488.60	3,863.68	799.88	1,825.03	16	5,776.58	3,440.02	709.58	1,626.98
17	6,479.43	3,863.03	796.45	1,819.95	17	5,749.83	3,433.50	705.62	1,610.72
18	6,492.15	3,873.12	795.32	1,823.72	18	5,751.58	3,424.53	710.07	1,616.98
19	6,471.80	3,860.97	790.50	1,820.33	19	5,760.97	3,434.72	707.05	1,619.20

Response Time Ramp Distribution (IOPS) Data (continued)

50% Load Level - 720 BSUs					10% Load Level - 144 BSUs				
Start-Up/Ramp-Up	Start	Stop	Interval	Duration	Start-Up/Ramp-Up	Start	Stop	Interval	Duration
Measurement Interval	19:35:26	19:45:26	10-19	0:10:00	Measurement Interval	19:55:28	20:05:28	10-19	0:10:00
(60 second intervals)	All ASUs	ASU-1	ASU-2	ASU-3	(60 second intervals)	All ASUs	ASU-1	ASU-2	ASU-3
0	3,603.73	2,150.00	442.13	1,011.60	0	715.58	425.43	88.80	201.35
1	3,603.15	2,145.85	444.02	1,013.28	1	724.02	433.15	89.37	201.50
2	3,594.05	2,142.85	444.77	1,006.43	2	722.47	431.03	87.88	203.55
3	3,612.48	2,160.52	443.83	1,008.13	3	710.98	422.87	86.30	201.82
4	3,601.47	2,151.07	443.18	1,007.22	4	719.42	425.72	90.48	203.22
5	3,603.85	2,142.08	446.38	1,015.38	5	721.95	432.65	90.03	199.27
6	3,600.33	2,146.92	440.27	1,013.15	6	717.20	424.93	90.20	202.07
7	3,592.12	2,135.57	446.05	1,010.50	7	719.10	430.30	87.78	201.02
8	3,589.43	2,144.05	436.27	1,009.12	8	716.12	426.55	87.17	202.40
9	3,599.22	2,144.57	441.75	1,012.90	9	722.58	429.92	90.83	201.83
10	3,586.53	2,138.30	444.53	1,003.70	10	722.50	430.80	89.48	202.22
11	3,598.95	2,149.95	444.72	1,004.28	11	725.17	432.90	88.20	204.07
12	3,591.18	2,135.67	443.22	1,012.30	12	716.25	426.32	88.62	201.32
13	3,589.35	2,145.80	437.05	1,006.50	13	719.88	427.37	89.08	203.43
14	3,601.12	2,148.78	442.17	1,010.17	14	718.95	429.48	88.93	200.53
15	3,602.08	2,150.77	444.32	1,007.00	15	722.78	432.17	89.05	201.57
16	3,609.33	2,146.93	448.23	1,014.17	16	718.62	426.67	89.28	202.67
17	3,606.67	2,149.70	440.90	1,016.07	17	716.48	427.90	87.90	200.68
18	3,604.85	2,147.68	445.78	1,011.38	18	715.73	427.80	87.35	200.58
19	3,607.78	2,149.38	439.85	1,018.55	19	715.93	428.97	89.40	197.57
Average	3,599.79	2,146.30	443.08	1,010.41	Average	719.23	429.04	88.73	201.46


Response Time Ramp Distribution (IOPS) Graph



SPC-1C LRT™ Average Response Time (ms) Distribution Data

144 BSUs	Start	Stop	Interval	Duration
<i>Start-Up/Ramp-Up</i>	19:45:27	19:55:28	0-9	0:10:01
<i>Measurement Interval</i>	19:55:28	20:05:28	10-19	0:10:00
60 second intervals	All ASUs	ASU1	ASU2	ASU3
0	0.94	1.20	1.65	0.09
1	0.82	1.05	1.38	0.08
2	0.83	1.08	1.40	0.07
3	0.81	1.05	1.35	0.07
4	0.81	1.06	1.31	0.08
5	0.81	1.03	1.31	0.09
6	0.82	1.05	1.39	0.07
7	0.81	1.06	1.30	0.07
8	0.81	1.06	1.30	0.07
9	0.80	1.04	1.29	0.07
10	0.83	1.08	1.30	0.09
11	0.79	1.03	1.28	0.07
12	0.80	1.05	1.25	0.07
13	0.81	1.06	1.27	0.07
14	0.80	1.03	1.31	0.07
15	0.77	1.01	1.19	0.08
16	0.77	1.01	1.25	0.07
17	0.76	1.00	1.16	0.07
18	0.77	1.00	1.18	0.08
19	0.77	1.00	1.18	0.08
Average	0.79	1.03	1.24	0.08

SPC-1C LRT™ Average Response Time (ms) Distribution Graph



SPC-1C LRT™ (10%) – Measured Intensity Multiplier and Coefficient of Variation

Clause 3.4.3

IM – Intensity Multiplier: The ratio of I/Os for each I/O stream relative to the total I/Os for all I/O streams (ASU1-1 – ASU3-1) as required by the benchmark specification.

Clauses 6.1.10

MIM – Measured Intensity Multiplier: The Measured Intensity Multiplier represents the ratio of measured I/Os for each I/O stream relative to the total I/Os measured for all I/O streams (ASU1-1 – ASU3-1).

Clause 6.3.14.3

COV – Coefficient of Variation: This measure of variation for the Measured Intensity Multiplier cannot exceed 0.5.

	ASU1-1	ASU1-2	ASU1-3	ASU1-4	ASU2-1	ASU2-2	ASU2-3	ASU3-1
IM	0.0350	0.2810	0.0700	0.2100	0.0180	0.0700	0.0350	0.2810
MIM	0.0352	0.2824	0.0693	0.2095	0.0182	0.0702	0.0349	0.2801
COV	0.022	0.010	0.017	0.009	0.020	0.010	0.014	0.007

Repeatability Test

Clause 6.4.4

The Repeatability Test demonstrates the repeatability and reproducibility of the SPC-1C IOPS™ primary metric and SPC-1C LRT™ metric generated in earlier Test Runs.

There are two identical Repeatability Test Phases. Each Test Phase contains two Test Runs. Each of the Test Runs will have a Measurement Interval of no less than five (5) minutes. The two Test Runs in each Test Phase will be executed without interruption or any type of manual intervention.

The first Test Run in each Test Phase is executed at the 10% load point. The Average Response Time from each of the Test Runs is compared to the SPC-1C LRT™ metric. Each Average Response Time value must be less than the SPC-1C LRT™ metric plus 5%.

The second Test Run in each Test Phase is executed at the 100% load point. The I/O Request Throughput from the Test Runs is compared to the SPC-1C IOPS™ primary metric. Each I/O Request Throughput value must be greater than the SPC-1C IOPS™ primary metric minus 5%. In addition, the Average Response Time for each Test Run cannot exceed 30 milliseconds.

If any of the above constraints are not met, the benchmark measurement is invalid.

Clause 10.4.8.5

The FDR shall contain the following for the Repeatability Test:

- 1. A table containing the results of the Repeatability Test.*
- 2. I/O Request Throughput Distribution graph and table for each Repeatability Test Run.*
- 3. An Average Response Time Distribution graph and table for each Repeatability Test Run.*
- 4. The human readable Test Run Results File produced by the Workload Generator. The human readable Test Run Results File produced by the SPC-1C C Workload Generator.*
- 5. A listing of all input parameters supplied to the SPC-1C Workload Generator.*

SPC-1C Workload Generator Input Parameters

The SPC-1C Workload Generator input parameters for the Sustainability, IOPS, Response Time Ramp, Repeatability, and Persistence Test Runs are documented in [Appendix E: SPC-1C Workload Generator Input Parameters](#) on Page [74](#).

Repeatability Test Results File

The values for the SPC-1C IOPS™, SPC-1C LRT™, and the Repeatability Test measurements are listed in the tables below.

	SPC-1C IOPS™
Primary Metrics	7,197.38
Repeatability Test Phase 1	7,198.34
Repeatability Test Phase 2	7,198.35

The SPC-1C IOPS™ values in the above table were generated using 100% of the specified Business Scaling Unit (BSU) load level. Each of the Repeatability Test Phase values for SPC-1C IOPS™ must be greater than 95% of the reported SPC-1C IOPS™ Primary Metric.

	SPC-1C LRT™
Primary Metrics	0.79 ms
Repeatability Test Phase 1	0.76 ms
Repeatability Test Phase 2	0.73 ms

The average response time values in the SPC-1C LRT™ column were generated using 10% of the specified Business Scaling Unit (BSU) load level. Each of the Repeatability Test Phase values for SPC-1C LRT™ must be less than 105% of the reported SPC-1C LRT™ Primary Metric or less than the reported SPC-1C LRT™ Primary Metric minus one (1) millisecond (ms).


A link to the test result file generated from each Repeatability Test Run is listed below.

- [Repeatability Test Phase 1, Test Run 1 \(LRT\)](#)
- [Repeatability Test Phase 1, Test Run 2 \(IOPS\)](#)
- [Repeatability Test Phase 2, Test Run 1 \(LRT\)](#)
- [Repeatability Test Phase 2, Test Run 2 \(IOPS\)](#)

Repeatability 1 LRT – I/O Request Throughput Distribution Data

144 BSUs	Start	Stop	Interval	Duration
<i>Start-Up/Ramp-Up</i>	20:05:31	20:15:31	0-9	0:10:00
<i>Measurement Interval</i>	20:15:31	20:35:31	10-29	0:20:00
60 second intervals	All ASUs	ASU1	ASU2	ASU3
0	723.90	432.63	88.33	202.93
1	721.40	425.43	89.15	206.82
2	718.92	430.22	87.65	201.05
3	718.90	424.40	90.47	204.03
4	717.87	429.08	89.15	199.63
5	717.45	427.93	89.80	199.72
6	719.87	430.72	87.28	201.87
7	724.72	433.13	88.88	202.70
8	716.13	425.80	89.25	201.08
9	713.55	428.68	86.10	198.77
10	723.75	428.37	91.18	204.20
11	717.65	427.13	89.12	201.40
12	719.88	429.02	89.52	201.35
13	716.68	426.67	88.17	201.85
14	717.60	425.53	89.32	202.75
15	722.28	431.40	87.42	203.47
16	716.70	428.67	88.18	199.85
17	722.98	429.65	87.90	205.43
18	721.50	429.42	89.22	202.87
19	725.20	432.23	91.63	201.33
20	716.70	425.80	89.43	201.47
21	720.13	429.05	87.28	203.80
22	719.67	430.07	89.17	200.43
23	721.25	429.58	90.52	201.15
24	719.97	429.57	87.90	202.50
25	718.22	424.78	90.30	203.13
26	724.07	429.70	89.60	204.77
27	720.63	429.35	88.63	202.65
28	717.17	428.78	88.15	200.23
29	715.97	427.68	88.52	199.77
Average	719.90	428.62	89.06	202.22


Repeatability 1 LRT – I/O Request Throughput Distribution Graph



Repeatability 1 LRT –Average Response Time (ms) Distribution Data

144 BSUs	Start	Stop	Interval	Duration
Start-Up/Ramp-Up	20:05:31	20:15:31	0-9	0:10:00
Measurement Interval	20:15:31	20:35:31	10-29	0:20:00
60 second intervals	All ASUs	ASU1	ASU2	ASU3
0	0.97	1.24	1.67	0.09
1	0.85	1.12	1.41	0.07
2	0.86	1.12	1.35	0.08
3	0.86	1.13	1.36	0.09
4	0.84	1.10	1.34	0.07
5	0.89	1.15	1.39	0.09
6	0.83	1.08	1.38	0.07
7	0.83	1.08	1.34	0.07
8	0.83	1.10	1.29	0.07
9	0.82	1.08	1.29	0.07
10	0.83	1.08	1.32	0.10
11	0.84	1.12	1.31	0.07
12	0.81	1.06	1.29	0.07
13	0.81	1.06	1.26	0.07
14	0.80	1.05	1.28	0.06
15	0.79	1.04	1.23	0.09
16	0.77	0.99	1.30	0.07
17	0.76	0.99	1.26	0.07
18	0.75	0.96	1.25	0.08
19	0.75	0.96	1.22	0.08
20	0.76	0.98	1.21	0.09
21	0.72	0.92	1.26	0.07
22	0.73	0.92	1.28	0.07
23	0.71	0.92	1.18	0.07
24	0.71	0.91	1.18	0.07
25	0.72	0.93	1.17	0.09
26	0.70	0.90	1.16	0.07
27	0.71	0.91	1.21	0.07
28	0.72	0.92	1.19	0.08
29	0.71	0.92	1.14	0.07
Average	0.76	0.98	1.23	0.08


Repeatability 1 LRT –Average Response Time (ms) Distribution Graph



Repeatability 1 IOPS – I/O Request Throughput Distribution Data

1,440 BSUs	Start	Stop	Interval	Duration
<i>Start-Up/Ramp-Up</i>	20:35:33	20:45:34	0-9	0:10:01
<i>Measurement Interval</i>	20:45:34	21:05:34	10-29	0:20:00
60 second intervals	All ASUs	ASU1	ASU2	ASU3
0	7,184.03	4,286.13	885.62	2,012.28
1	7,201.65	4,285.78	881.97	2,033.90
2	7,186.93	4,282.63	883.95	2,020.35
3	7,194.38	4,284.10	888.70	2,021.58
4	7,199.77	4,280.98	886.35	2,032.43
5	7,197.47	4,292.50	889.98	2,014.98
6	7,191.63	4,277.97	884.98	2,028.68
7	7,205.02	4,295.63	879.65	2,029.73
8	7,206.72	4,304.50	881.43	2,020.78
9	7,197.28	4,290.67	888.27	2,018.35
10	7,203.33	4,302.50	878.38	2,022.45
11	7,202.05	4,294.57	889.30	2,018.18
12	7,202.03	4,296.23	888.72	2,017.08
13	7,191.70	4,296.65	882.10	2,012.95
14	7,202.55	4,288.15	881.97	2,032.43
15	7,187.23	4,279.18	880.43	2,027.62
16	7,185.62	4,282.67	882.63	2,020.32
17	7,198.42	4,297.48	883.98	2,016.95
18	7,219.35	4,301.28	886.27	2,031.80
19	7,202.45	4,288.13	888.30	2,026.02
20	7,175.33	4,270.77	887.20	2,017.37
21	7,196.17	4,287.15	884.63	2,024.38
22	7,199.90	4,285.65	890.78	2,023.47
23	7,202.67	4,301.37	881.77	2,019.53
24	7,218.62	4,301.93	886.10	2,030.58
25	7,195.00	4,281.27	886.83	2,026.90
26	7,190.05	4,277.95	890.77	2,021.33
27	7,201.15	4,283.72	891.33	2,026.10
28	7,199.27	4,291.55	885.55	2,022.17
29	7,193.95	4,293.72	880.52	2,019.72
Average	7,198.34	4,290.10	885.38	2,022.87


Repeatability 1 IOPS – I/O Request Throughput Distribution Graph



Repeatability 1 IOPS –Average Response Time (ms) Distribution Data

1,440 BSUs	Start	Stop	Interval	Duration
<i>Start-Up/Ramp-Up</i>	20:35:33	20:45:34	0-9	0:10:01
<i>Measurement Interval</i>	20:45:34	21:05:34	10-29	0:20:00
60 second intervals	All ASUs	ASU1	ASU2	ASU3
0	13.22	14.58	26.86	4.33
1	9.34	10.99	15.97	2.98
2	8.91	10.40	16.11	2.61
3	8.52	9.91	15.11	2.70
4	7.67	9.11	13.42	2.14
5	8.17	9.62	13.59	2.67
6	7.77	9.29	13.39	2.13
7	7.77	9.20	13.03	2.45
8	7.59	8.97	13.25	2.18
9	7.45	8.79	12.80	2.23
10	7.46	8.74	13.48	2.14
11	7.43	8.78	12.87	2.15
12	7.06	8.31	12.33	2.09
13	6.97	8.23	12.04	2.06
14	7.10	8.43	12.17	2.09
15	6.91	8.19	12.01	1.98
16	6.94	8.26	11.95	1.97
17	6.85	8.18	11.75	1.87
18	7.04	8.18	12.34	2.32
19	6.98	8.13	11.96	2.37
20	6.89	8.16	11.65	2.11
21	6.84	7.97	11.82	2.28
22	6.88	8.07	11.53	2.29
23	6.46	7.72	10.89	1.83
24	6.98	8.18	11.83	2.32
25	7.17	8.50	11.76	2.33
26	7.00	8.35	11.52	2.15
27	6.94	8.16	11.54	2.34
28	6.66	7.92	11.02	2.08
29	6.43	7.68	10.66	1.92
Average	6.95	8.21	11.86	2.13


Repeatability 1 IOPS –Average Response Time (ms) Distribution Graph



Repeatability 2 LRT – I/O Request Throughput Distribution Data

144 BSUs	Start	Stop	Interval	Duration
<i>Start-Up/Ramp-Up</i>	21:05:38	21:15:38	0-9	0:10:00
<i>Measurement Interval</i>	21:15:38	21:35:38	10-39	0:20:00
60 second intervals	All ASUs	ASU1	ASU2	ASU3
0	720.25	430.35	86.65	203.25
1	719.37	428.68	88.70	201.98
2	718.62	427.63	86.90	204.08
3	720.50	429.27	89.45	201.78
4	725.70	434.20	89.55	201.95
5	718.60	429.10	86.67	202.83
6	717.12	425.42	88.70	203.00
7	722.80	427.40	89.60	205.80
8	721.22	433.08	87.00	201.13
9	723.65	433.17	88.08	202.40
10	719.47	426.73	87.70	205.03
11	715.80	425.53	88.35	201.92
12	719.13	428.08	87.05	204.00
13	719.82	430.02	87.45	202.35
14	724.63	434.75	89.83	200.05
15	723.47	430.40	89.53	203.53
16	723.80	430.48	88.28	205.03
17	725.47	431.45	89.53	204.48
18	722.70	431.05	88.72	202.93
19	720.32	430.15	86.80	203.37
20	720.47	432.95	88.53	198.98
21	719.75	427.63	90.12	202.00
22	729.02	439.62	88.05	201.35
23	721.38	427.43	89.67	204.28
24	717.38	429.68	87.67	200.03
25	721.48	428.87	88.93	203.68
26	717.77	428.13	88.93	200.70
27	716.15	427.28	86.98	201.88
28	720.12	430.02	89.07	201.03
29	717.40	426.57	84.90	205.93
Average	720.78	429.84	88.31	202.63


Repeatability 2 LRT – I/O Request Throughput Distribution Graph



Repeatability 2 LRT –Average Response Time (ms) Distribution Data

144 BSUs	Start	Stop	Interval	Duration
<i>Start-Up/Ramp-Up</i>	21:05:38	21:15:38	0-9	0:10:00
<i>Measurement Interval</i>	21:15:38	21:35:38	10-39	0:20:00
60 second intervals	All ASUs	ASU1	ASU2	ASU3
0	0.93	1.19	1.62	0.09
1	0.84	1.07	1.43	0.08
2	0.84	1.09	1.39	0.08
3	0.84	1.10	1.33	0.07
4	0.84	1.08	1.36	0.07
5	0.82	1.05	1.37	0.09
6	0.80	1.02	1.34	0.09
7	0.77	1.00	1.28	0.07
8	0.77	0.99	1.29	0.07
9	0.77	0.99	1.28	0.07
10	0.78	1.00	1.26	0.10
11	0.76	1.00	1.24	0.07
12	0.74	0.95	1.30	0.07
13	0.74	0.95	1.27	0.07
14	0.76	0.96	1.30	0.07
15	0.73	0.94	1.22	0.08
16	0.72	0.93	1.23	0.07
17	0.72	0.92	1.20	0.08
18	0.74	0.95	1.26	0.07
19	0.71	0.92	1.23	0.07
20	0.74	0.95	1.23	0.08
21	0.75	0.96	1.25	0.07
22	0.72	0.93	1.21	0.07
23	0.69	0.89	1.19	0.07
24	0.71	0.91	1.14	0.07
25	0.73	0.95	1.17	0.08
26	0.74	0.96	1.17	0.07
27	0.71	0.92	1.16	0.08
28	0.71	0.94	1.09	0.07
29	0.70	0.92	1.14	0.07
Average	0.73	0.94	1.21	0.07


Repeatability 2 LRT –Average Response Time (ms) Distribution Graph



Repeatability 2 IOPS – I/O Request Throughput Distribution Data

1,440 BSUs	Start	Stop	Interval	Duration
<i>Start-Up/Ramp-Up</i>	21:35:40	21:45:41	0-9	0:10:01
<i>Measurement Interval</i>	21:45:41	22:05:41	10-29	0:20:00
60 second intervals	All ASUs	ASU1	ASU2	ASU3
0	7,207.67	4,287.85	885.65	2,034.17
1	7,209.78	4,293.28	879.50	2,037.00
2	7,200.10	4,293.52	883.42	2,023.17
3	7,218.78	4,301.50	884.42	2,032.87
4	7,203.50	4,300.88	884.47	2,018.15
5	7,199.30	4,286.57	889.02	2,023.72
6	7,212.30	4,306.45	888.40	2,017.45
7	7,180.78	4,281.43	885.58	2,013.77
8	7,197.33	4,287.82	884.90	2,024.62
9	7,186.85	4,281.77	885.03	2,020.05
10	7,215.57	4,297.42	889.12	2,029.03
11	7,192.53	4,285.08	880.00	2,027.45
12	7,192.57	4,288.27	891.02	2,013.28
13	7,189.35	4,284.90	882.15	2,022.30
14	7,191.27	4,287.33	889.73	2,014.20
15	7,188.28	4,283.47	885.15	2,019.67
16	7,193.25	4,277.27	888.28	2,027.70
17	7,213.27	4,299.87	883.12	2,030.28
18	7,205.23	4,294.83	880.75	2,029.65
19	7,201.60	4,289.48	887.97	2,024.15
20	7,197.53	4,292.85	887.35	2,017.33
21	7,202.37	4,291.53	879.50	2,031.33
22	7,193.60	4,289.40	882.27	2,021.93
23	7,193.50	4,282.50	889.47	2,021.53
24	7,202.40	4,292.87	884.05	2,025.48
25	7,204.40	4,293.53	885.28	2,025.58
26	7,195.10	4,292.53	884.98	2,017.58
27	7,209.77	4,291.25	886.72	2,031.80
28	7,175.02	4,268.58	885.68	2,020.75
29	7,210.45	4,306.85	878.78	2,024.82
Average	7,198.35	4,289.49	885.07	2,023.79


Repeatability 2 IOPS – I/O Request Throughput Distribution Graph



Repeatability 2 IOPS –Average Response Time (ms) Distribution Data

1,440 BSUs	Start	Stop	Interval	Duration
Start-Up/Ramp-Up	21:35:40	21:45:41	0-9	0:10:01
Measurement Interval	21:45:41	22:05:41	10-29	0:20:00
60 second intervals	All ASUs	ASU1	ASU2	ASU3
0	13.31	14.76	26.57	4.50
1	9.28	10.87	16.68	2.75
2	9.30	10.83	16.85	2.75
3	9.07	10.76	16.20	2.38
4	8.10	9.52	14.48	2.27
5	8.06	9.51	14.27	2.26
6	8.07	9.44	14.31	2.38
7	7.75	9.17	13.51	2.21
8	7.83	9.33	13.54	2.14
9	7.46	8.91	13.20	1.86
10	7.89	9.44	13.35	2.22
11	7.76	9.30	13.57	1.97
12	7.40	8.81	12.62	2.08
13	7.29	8.64	12.73	2.05
14	7.44	8.82	12.96	2.07
15	7.25	8.57	12.63	2.09
16	7.16	8.48	12.33	2.10
17	7.39	8.62	12.95	2.36
18	6.86	8.10	12.03	1.99
19	7.17	8.48	12.35	2.10
20	7.20	8.43	12.43	2.28
21	6.99	8.31	12.28	1.92
22	6.94	8.29	11.79	1.96
23	7.06	8.40	12.03	2.02
24	6.78	8.14	11.16	1.97
25	7.08	8.35	11.91	2.29
26	6.83	8.17	11.42	1.97
27	7.13	8.50	11.71	2.23
28	6.62	7.99	10.57	1.98
29	6.62	7.90	11.15	1.95
Average	7.14	8.49	12.20	2.08

Repeatability 2 IOPS –Average Response Time (ms) Distribution Graph



Repeatability 1 (LRT)
Measured Intensity Multiplier and Coefficient of Variation

Clause 3.4.3

IM – Intensity Multiplier: The ratio of I/Os for each I/O stream relative to the total I/Os for all I/O streams (ASU1-1 – ASU3-1) as required by the benchmark specification.

Clauses 6.1.10

MIM – Measured Intensity Multiplier: The Measured Intensity Multiplier represents the ratio of measured I/Os for each I/O stream relative to the total I/Os measured for all I/O streams (ASU1-1 – ASU3-1).

Clause 6.3.14.3

COV – Coefficient of Variation: This measure of variation for the Measured Intensity Multiplier cannot exceed 0.5.

	ASU1-1	ASU1-2	ASU1-3	ASU1-4	ASU2-1	ASU2-2	ASU2-3	ASU3-1
IM	0.0350	0.2810	0.0700	0.2100	0.0180	0.0700	0.0350	0.2810
MIM	0.0346	0.2811	0.0698	0.2099	0.0182	0.0705	0.0350	0.2809
COV	0.026	0.005	0.015	0.007	0.040	0.014	0.023	0.006

Repeatability 1 (IOPS)
Measured Intensity Multiplier and Coefficient of Variation

	ASU1-1	ASU1-2	ASU1-3	ASU1-4	ASU2-1	ASU2-2	ASU2-3	ASU3-1
IM	0.0350	0.2810	0.0700	0.2100	0.0180	0.0700	0.0350	0.2810
MIM	0.0350	0.2809	0.0701	0.2100	0.0180	0.0699	0.0352	0.2810
COV	0.009	0.002	0.005	0.003	0.012	0.007	0.008	0.002

Repeatability 2 (LRT)
Measured Intensity Multiplier and Coefficient of Variation

	ASU1-1	ASU1-2	ASU1-3	ASU1-4	ASU2-1	ASU2-2	ASU2-3	ASU3-1
IM	0.0350	0.2810	0.0700	0.2100	0.0180	0.0700	0.0350	0.2810
MIM	0.0350	0.2810	0.0705	0.2099	0.0181	0.0695	0.0349	0.2811
COV	0.022	0.008	0.014	0.010	0.038	0.015	0.027	0.010

Repeatability 2 (IOPS)
Measured Intensity Multiplier and Coefficient of Variation

	ASU1-1	ASU1-2	ASU1-3	ASU1-4	ASU2-1	ASU2-2	ASU2-3	ASU3-1
<i>IM</i>	<i>0.0350</i>	<i>0.2810</i>	<i>0.0700</i>	<i>0.2100</i>	<i>0.0180</i>	<i>0.0700</i>	<i>0.0350</i>	<i>0.2810</i>
MIM	0.0350	0.2808	0.0701	0.2100	0.0179	0.0701	0.0350	0.2811
COV	0.008	0.003	0.006	0.003	0.011	0.006	0.007	0.002

Data Persistence Test

Clause 7

The Data Persistence Test demonstrates the Tested Storage Configuration (TSC):

- *Is capable of maintain data integrity across a power cycle.*
- *Ensures the transfer of data between Logical Volumes and host systems occurs without corruption or loss.*

The SPC-1C Workload Generator will write 16 block I/O requests at random over the total Addressable Storage Capacity of the TSC for ten (10) minutes at a minimum of 25% of the load used to generate the SPC-1C IOPS™ primary metric. The bit pattern selected to be written to each block as well as the address of the block will be retained in a log file.

The Tested Storage Configuration will be shutdown and restarted using a power off/power on cycle at the end of the above sequence of write operations. In addition, any caches employing battery backup must be flushed/emptied.

The SPC-1C Workload Generator will then use the above log file to verify each block written contains the correct bit pattern.

Clause 10.4.8.6

The FDR shall contain the following for the Data Persistence Test:

1. *A listing of the SPC-1C Workload Generator commands and parameters used to execute each of the Test Runs in the Persistence Test.*
2. *The human readable SPC-1C Test Results File for each of the Test Runs in the Data Persistence Test.*
3. *A table from the successful Persistence Test, which contains the results from the test.*

SPC-1C Workload Generator Input Parameters

The SPC-1C Workload Generator input parameters for the Sustainability, IOPS, Response Time Ramp, Repeatability, and Persistence Test Runs are documented in [Appendix E: SPC-1C Workload Generator Input Parameters](#) on Page [74](#).

Data Persistence Test Results File

A link to each test result file generated from each Data Persistence Test is listed below.

[Persistence 1 Test Results File](#)

[Persistence 2 Test Results File](#)

Data Persistence Test Results

Data Persistence Test Results	
Data Persistence Test Run Number: 1	
Total Number of Logical Blocks Written	17,305,425
Total Number of Logical Blocks Verified	16,688,688
Total Number of Logical Blocks that Failed Verification	0
Time Duration for Writing Test Logical Blocks	10 minutes
Size in bytes of each Logical Block	512
Number of Failed I/O Requests in the process of the Test	0

In some cases the same address was the target of multiple writes, which resulted in more Logical Blocks Written than Logical Blocks Verified. In the case of multiple writes to the same address, the pattern written and verified must be associated with the last write to that address.

PRICED STORAGE CONFIGURATION AVAILABILITY DATE

Clause 10.4.9

The committed delivery date for general availability (Availability Date) of all products that comprise the Priced Storage Configuration must be reported. When the Priced Storage Configuration includes products or components with different availability dates, the reported Availability Date must be the date at which all components are committed to be available. All availability dates, whether for individual components or for the Priced Storage Configuration as a whole, must be disclosed to a precision of one day.

The Availability Date shall be stated in the FDR by either a combination of specific alphanumeric month, numeric day, and numeric year or as "Currently Available" in the case where all components that comprise the Priced Storage Configuration are currently available for customer order and shipment.

The Seagate ST600MX0004 600GB 15K 6Gbps SAS 2.5" SSHD Hybrid as documented in this Full Disclosure Report will become available on January 15, 2014 for customer purchase and shipment.

PRICING INFORMATION

Clause 10.4.5.6

The Executive Summary shall contain a pricing spreadsheet as documented in Clause 9.3.1.

Pricing information may be found in the Priced Storage Configuration Pricing section on page 17.

TESTED STORAGE CONFIGURATION (TSC) AND PRICED STORAGE CONFIGURATION DIFFERENCES

Clause 10.4.5.8

The Executive Summary shall contain a list of all differences between the Tested Storage Configuration (TSC) and the Priced Storage Configuration.

A list of all differences between the Tested Storage Configuration (TSC) and Priced Storage Configuration may be found in the Executive Summary portion of this document on page 17.

ANOMALIES OR IRREGULARITIES

Clause 10.4.10

The FDR shall include a clear and complete description of any anomalies or irregularities encountered in the course of executing the SPC-1C benchmark that may in any way call into question the accuracy, verifiability, or authenticity of information published in the FDR.

There were no anomalies or irregularities encountered during the SPC-1C Onsite Audit of the Seagate ST600MX0004 600GB 15K 6Gbps SAS 2.5" SSHD Hybrid.

APPENDIX A: SPC-1C GLOSSARY

“Decimal” (*powers of ten*) Measurement Units

In the storage industry, the terms “kilo”, “mega”, “giga”, “tera”, “peta”, and “exa” are commonly used prefixes for computing performance and capacity. For the purposes of the SPC workload definitions, all of the following terms are defined in “powers of ten” measurement units.

A kilobyte (KB) is equal to 1,000 (10^3) bytes.

A megabyte (MB) is equal to 1,000,000 (10^6) bytes.

A gigabyte (GB) is equal to 1,000,000,000 (10^9) bytes.

A terabyte (TB) is equal to 1,000,000,000,000 (10^{12}) bytes.

A petabyte (PB) is equal to 1,000,000,000,000,000 (10^{15}) bytes

An exabyte (EB) is equal to 1,000,000,000,000,000,000 (10^{18}) bytes

“Binary” (*powers of two*) Measurement Units

The sizes reported by many operating system components use “powers of two” measurement units rather than “power of ten” units. The following standardized definitions and terms are also valid and may be used in this document.

A kibibyte (KiB) is equal to 1,024 (2^{10}) bytes.

A mebibyte (MiB) is equal to 1,048,576 (2^{20}) bytes.

A gibibyte (GiB) is equal to 1,073,741,824 (2^{30}) bytes.

A tebibyte (TiB) is equal to 1,099,511,627,776 (2^{40}) bytes.

A pebibyte (PiB) is equal to 1,125,899,906,842,624 (2^{50}) bytes.

An exbibyte (EiB) is equal to 1,152,921,504,606,846,967 (2^{60}) bytes.

SPC-1C Data Repository Definitions

Total ASU Capacity: The total storage capacity read and written in the course of executing the SPC-1C benchmark.

Application Storage Unit (ASU): The logical interface between the storage and SPC-1C Workload Generator. The three ASUs (Data, User, and Log) are typically implemented on one or more Logical Volume.

Logical Volume: The division of Addressable Storage Capacity into individually addressable logical units of storage used in the SPC-1C benchmark. Each Logical Volume is implemented as a single, contiguous address space.

Addressable Storage Capacity: The total storage (sum of Logical Volumes) that can be read and written by application programs such as the SPC-1C Workload Generator.

Configured Storage Capacity: This capacity includes the Addressable Storage Capacity and any other storage (parity disks, hot spares, etc.) necessary to implement the Addressable Storage Capacity.

Physical Storage Capacity: The formatted capacity of all storage devices physically present in the Tested Storage Configuration (TSC).

Data Protection Overhead: The storage capacity required to implement the selected level of data protection.

Required Storage: The amount of Configured Storage Capacity required to implement the Addressable Storage Configuration, excluding the storage required for the three ASUs.

Global Storage Overhead: The amount of Physical Storage Capacity that is required for storage subsystem use and unavailable for use by application programs.

Total Unused Storage: The amount of storage capacity available for use by application programs but not included in the Total ASU Capacity.

SPC-1C Data Protection Levels

Protected 1: The single point of failure of any *storage device* in the configuration will not result in permanent loss of access to or integrity of the SPC-1C Data Repository.

Protected 2: The single point of failure of any *component* in the configuration will not result in permanent loss of access to or integrity of the SPC-1C Data Repository.

Unprotected: The Test Sponsor asserts no claim of data protection in the event of a single point of failure.

SPC-1C Test Execution Definitions

Average Response Time: The sum of the Response Times for all Measured I/O Requests divided by the total number of Measured I/O Requests.

Completed I/O Request: An I/O Request with a Start Time and a Completion Time (see “I/O Completion Types” below).

Completion Time: The time recorded by the Workload Generator when an I/O Request is satisfied by the TSC as signaled by System Software.

Data Rate: The data transferred in all Measured I/O Requests in an SPC-1C Test Run divided by the length of the Test Run in seconds.

Expected I/O Count: For any given I/O Stream and Test Phase, the product of 50 times the BSU level, the duration of the Test Phase in seconds, and the Intensity Multiplier for that I/O Stream.

Failed I/O Request: Any I/O Request issued by the Workload Generator that could not be completed or was signaled as failed by System Software. A Failed I/O Request has no Completion Time (see “I/O Completion Types” below).

I/O Request Throughput: The total number of Measured I/O requests in an SPC-1C Test Run divided by the duration of the Measurement Interval in seconds.

In-Flight I/O Request: An I/O Request issued by the I/O Command Generator to the TSC that has a recorded Start Time, but does not complete within the Measurement Interval (see “I/O Completion Types” below).

Measured I/O Request: A Completed I/O Request with a Completion Time occurring within the Measurement Interval (see “I/O Completion Types” below).

Measured Intensity Multiplier: The percentage of all Measured I/O Requests that were issued by a given I/O Stream.

Measurement Interval: The finite and contiguous time period, after the TSC has reached Steady State, when data is collected by a Test Sponsor to generate an SPC-1C test result or support an SPC-1C test result.

Ramp-Up: The time required for the Benchmark Configuration (BC) to produce Steady State throughput after the Workload Generator begins submitting I/O Requests to the TSC for execution.

Ramp-Down: The time required for the BC to complete all I/O Requests issued by the Workload Generator. The Ramp-Down period begins when the Workload Generator ceases to issue new I/O Requests to the TSC.

Response Time: The Response Time of a Measured I/O Request is its Completion Time minus its Start Time.

Start Time: The time recorded by the Workload Generator when an I/O Request is submitted, by the Workload Generator, to the System Software for execution on the Tested Storage Configuration (TSC).

Start-Up: The period that begins after the Workload Generator starts to submit I/O requests to the TSC and ends at the beginning of the Measurement Interval.

Shut-Down: The period between the end of the Measurement Interval and the time when all I/O Requests issued by the Workload Generator have completed or failed.

Steady State: The consistent and sustainable throughput of the TSC. During this period the load presented to the TSC by the Workload Generator is constant.


Test: A collection of Test Phases and or Test Runs sharing a common objective.

Test Run: The execution of SPC-1C for the purpose of producing or supporting an SPC-1C test result. SPC-1C Test Runs may have a finite and measured Ramp-Up period, Start-Up


period, Shut-Down period, and Ramp-Down period as illustrated in the “SPC-1C Test Run Components” below. All SPC-1C Test Runs shall have a Steady State period and a Measurement Interval.

Test Phase: A collection of one or more SPC-1C Test Runs sharing a common objective and intended to be run in a specific sequence.

I/O Completion Types



SPC-1C Test Run Components



APPENDIX B: CUSTOMER TUNABLE PARAMETERS AND OPTIONS

The customer tunable parameters and options that were changed for the benchmark measurements are documented in the [Change Parameters](#) section of [Appendix C: Tested Storage Configuration \(TSC\) Creation](#) on page [72](#).

APPENDIX C: TESTED STORAGE CONFIGURATION (TSC) CREATION

Create RAID-5 Array

Download the **MegaCLI (Command Line) Utility for Storage Management** from the IBM website at the following URL:

<http://www-947.ibm.com/support/entry/portal/docdisplay?lnocid=MIGR-5082326>

Execute the following script from the Host System, without any parameters, to create a RAID-5 array.

RB50.cmd

```
echo off
REM *****Clear All *****
MegaCLI64 -cfgclr -aALL
REM
REM Phys HDD List : 0,1,2,3 etc
REM Spares : NO
REM RAID Level : 50
REM Stripe Size : 256K
REM Array set Name :A0-A4
REM LD Read Policy : Read look ahead
REM LD Write Policy : Write Back, Bad BBU
REM LD IO Policy : Direct IO
REM Access Policy : Read / Write
REM *****
set adptr=0
set A0=-Array0[18:1,18:2,18:3,18:4]
set A1=-Array1[18:5,18:6,18:7,18:8]
set A2=-Array2[18:9,18:10,18:11,18:12]
set A3=-Array3[18:13,18:14,18:15,18:16]
set A4=-Array4[18:17,18:18,18:19,18:20]
set A5=-Array5[18:21,18:22,18:23,18:24]
set Arraylist=%A0% %A1% %A2% %A3% %A4% %A5%
set level=50
set stripe=256
set ReadCache=RA
set WriteCache=WB
Set BBU=CachedBadBBU
set IOpolicy=Direct
set access=RW
@echo on
REM ***** Create RAID 5 *****
MegaCli64 -CfgSpanAdd -r%level% %ArrayList% %WriteCache% %ReadCache% %IOpolicy%
%BBU% -strpsz%stripe% -a%adptr%
```

Create SPC-1C Logical Volumes

Invoke the Windows **DiskPart** command line utility, from a Windows command session, with the following command, which will execute the commands in **diskmkhdd.txt** to create the three SPC-1C Logical Volumes.

```
diskpart /s diskmkhdd.txt
```

diskmkhdd.txt

```
select disk 0
clean
convert gpt
create partition primary size=4631580 align=1024
create partition primary size=4631580 align=1024
create partition primary size=1029240 align=1024
select volume 2
assign letter=x
select volume 3
assign letter=y
select volume 4
assign letter=z
list volume
exit
```

Change Parameters

Execute the following MegaCLI script, without any parameters, from the Host System to create a change the appropriate user tunable parameter/options.

TuneParmBase.cmd

```
REM abort any background Initialization
MegaCli64 -LDBI -abort -Lall -aALL
REM
REM disable load balance i.e.configure as failover mode
MegaCli64 -AdpSetProp -LoadBalanceMode 1 -aALL
REM
REM disable background Initialization
MegaCli64 -LDBI -dsbl -Lall -aALL
REM
REM Enable WriteBack
megacli64 -ldsetprop WB -Lall -aALL
REM
REM Enable Diskcache
megacli64 -ldsetprop disdiskcache -Lall -aALL
```


APPENDIX D: SPC-1C WORKLOAD GENERATOR STORAGE COMMANDS AND PARAMETERS

ASU Pre-Fill

The content of command and parameter file, used in this benchmark to execute the required ASU pre-fill, is listed below.

```
*
sd=default,threads=32
sd=sd1,lun=\\.x:,size=4631580M
sd=sd2,lun=\\.y:,size=4631580M
sd=sd3,lun=\\.z:,size=1029240M
*
*
wd=wd1,sd=sd1,rdpct=0,seek=-1,xfersize=64k
wd=wd2,sd=sd2,rdpct=0,seek=-1,xfersize=64k
wd=wd3,sd=sd3,rdpct=0,seek=-1,xfersize=64k
*=====
* Use 10 hours as a max elapse time
*=====
*
*
rd=Prefill_ASUs,wd=wd*,iorate=max,elapsed=36000,interval=30
```

Primary Metrics Test, Repeatability and Persistence Tests

The content of SPC-1C Workload Generator command and parameter file, used in this benchmark to execute the Primary Metrics and Repeatability Tests, is listed below.

```
sd=asu1_1,lun=\\.x:
sd=asu2_1,lun=\\.y:
sd=asu3_1,lun=\\.z:
```

APPENDIX E: SPC-1C WORKLOAD GENERATOR INPUT PARAMETERS

Primary Metrics Test, Repeatability Test and Persistence Test Run 1

The following script was used to execute the required ASU Pre-Fill, Primary Metrics Test (*Sustainability Test Phase, IOPS Test Phase, and Response Time Ramp Test Phase*), Repeatability Test (*Repeatability Test Phase 1 and Repeatability Test Phase 2*), and SPC-1C Persistence Test Run 1 in an uninterrupted sequence.

```
rem prefill
cd c:\vd503rc11
call vdbench -f prefill.txt -o audit-prefill
cd c:\spc\spc1c
rem spc-1C
rem
set /a bsu=960
set java=c:\java\jre6\bin\java
echo
%java% -Xmx512m -Xms512m metrics -b %bsu% -t 28800 -s 600:600 -r 600
%java% -Xmx512m -Xms512m repeat1 -b %bsu% -t 1200 -s 600
%java% -Xmx512m -Xms512m repeat2 -b %bsu% -t 1200 -s 600
%java% -Xmx512m -Xms512m persist1 -b %bsu%
echo power cycle device then execute java -Xmx1g -Xss128k -Xms128m persist2
pause
REM %java% -Xmx512m -Xms512m persist2
```

Persistence Test Run 2

The following command was used to execute Persistence Test Run 2 from a CLI session.

```
c:\java\jre6\bin\java -Xmx512m -Xms512m persist2
```

APPENDIX F: THIRD-PARTY QUOTATIONS

Storage Enclosure

9/4/13
DNS-1640 2U-24 bay 6G 2.5" SAS/SATA JBOD


Better Storage • Agile Solution

[LOGIN](#) | [REGISTER](#)
 Contact Us: 1.877.512.0432 [search...](#)

DNS-1640 2U-24 bay 6G 2.5" SAS/SATA JBOD
Product Solution CIB Maxenta Server 2012 Partners Resource Support About US



DNS-1640

high-performance
green storage

This is replacement for DNS-1620

Introducing the newest addition to the DataON Product line the DNS-1640 (JBOD) Storage enclosure. The DNS-1640 is the core foundation for a Enterprise-Class, high performance, scalable and reliable 2.5" HDD & SSD storage solution.

Designed to meet the needs of continuing data growth, reliability and energy efficiency. DNS-1640 supports a "Start Small Grow Big" strategy by enabling users to connect DNS-1640 with DataON's Technology Partners HBA's for scalable storage.

DataON's expansion enclosure's are managed by the RAID controller or HBA in the primary server, they give IT administrators a cost-effective alternative to quickly respond to your demanding storage requirements.

DNS-1640 is the next generation storage enclosure to expand & scale your storage capacity beyond the server & maximize storage density, performance and power efficiency.

Features

- 2U 24-bay 2.5" 6Gb/s SAS & SATA HDDs or SSDs
- Redundant Hot Swap Drive Bays, Power & Cooling Module
- LED activity in Each Drive Carrier
- Single or Dual I/O Controller for Redundant and Max Availability
- Three SFF-8088 6Gb/s SAS host and expansion connections
- Supports up to 2,400 MB/sec bandwidth per I/O controller

Advantages

- High Performance, Flexible & Scalable Storage
- Fully Tested and Qualified for 6Gb/s SAS RAID & HBAs
- Point to Point SAS connectivity for Ultimate Performance
- Daisy Chain Expansion for additional DNS-1640
- Plug & Play Increase Capacity without shutting down
- Green Energy Efficient

Applications

- Audio and Video Post-Production
- Medical & Space Telescope Imaging
- High-Performance Computing
- Digital Content Archive & VTL
- File, Web, Database and E-mail Servers
- Online transaction processing (OLTP)

Model#	SAS I/O	Drive Bay	Drive Size	MSRP
DNS-1640D	Dual	24	2.5"	\$4,295.00
DNS-1640S	Single	24	2.5"	\$3,895.00

Copyright © 2009-2013 DataON Storage. All rights reserved.

www.dataonstorage.com/dataon-products/6g-sas-jbod/dns-1640-2u-24-bay-6g-25inch-sassata-jbod.html
1/2

LSI MegaRAID Controller

9/4/13
MegaRAID Controllers - 9265 Controllers


Region ▾ About LSI ▾

SOLUTIONS
PRODUCTS
INVENTION
SUPPORT
PARTNERS

LSI > Online Store > MegaRAID Controllers - 9265 Controllers

MegaRAID Controllers - 9265 Controllers

Controllers & Adapters

- » Host Bus Adapters
- » MegaRAID Controllers
- » 3ware Controllers
- » Syncro CS High Availability DAS
- » Clearance

Cables

- » Enclosure Management Cables
- » Internal Multi-Lane Cables
- » External Multi-Lane Cables
- » Clearance

Accessories

- » Battery Backup Unit (BBU)
- » CacheVault
- » Advanced Software Options
- » SAS Switch

Clearance

- » Clearance

MegaRAID SAS 9265-8i Kit



8-Port (Inf, 6Gb/s SATA+SAS, PCIe 3.0), 1GB DDRIII cache
In the Box:
MR SAS 9265-8i, cables, O/S, LP bracket, Documentation CD

Price: \$700.00 Add to cart Part #: LSI00278

8-Port (Inf, 6Gb/s SATA+SAS, PCIe 3.0), 1GB DDRIII cache
In the Box:
MR SAS 9265-8i, cables, O/S, LP bracket, Documentation CD

ACCESSORIES
TECHNICAL SPECS

Features

MegaRAID SAS 9265 Features

- Second generation 6Gb/s SATA+SAS with unprecedented levels of performance
- Ideal for internal storage environments using up to 128 SAS and SATA devices including HDDs and solid state drives (SSDs)
- Unsurpassed IOPs performance and advanced software options help users realize full benefits of SSD deployments
- Meets high I/O transaction demands of database and datacenter applications
- Provides the sustained data transfer rates and high sequential bandwidth to meet processing requirements of digital media, video and imaging environments

Specifications

Solution Provided:	Eight-port internal SAS solution for performance-hungry applications using up to 128 SAS, SATA and solid state drives (SSDs)
Physical Dimensions:	MD2 Low profile (6.8" X 2.536")
Internal Connectors:	Two Mini-SAS SFF8087 internal connectors
Device Support:	Up to 128 SAS and/or SATA hard drives and SSDs
Host Bus Type:	x8 lane PCI Express 2.0 compliant
Data Transfer Rates:	Up to 6Gb/s per port
I/O Processor/SAS Controller:	LSI SAS2208 Dual-Core RAID on Chip (ROC)
Cache Memory:	1 GB 1333MHz DDRIII SDRAM
Battery Backup Unit:	LSIBBU09, a heat-tolerant intelligent battery back-up module; (remote mount) <ul style="list-style-type: none"> • RAID levels 0, 1, 5, and 6 • RAID spans 10, 50, and 60 • Online Capacity Expansion (OCE) • Online RAID Level Migration (RLM) • Auto resume after loss of system power during arrays array rebuild or reconstruction (RLM) • Single controller Multipathing (failover) • Load Balancing • Configurable stripe size up to 1MB • Fast initialization for quick array setup • Check Consistency for background data integrity • SafeStore™ Encryption Services <ul style="list-style-type: none"> - Instant Secure Erase




SECURED BY
Geotrust
click to verify
04-Sep-13 13:24 GMT

https://store.lsi.com/store.cfm/MegaRAID_Controllers/9265_Controllers/LSI00278

1/4

SAS Cables

9/4/13
1m SFF-8087 to SFF-8088 SAS Cable - PC PitStop



Storage Solutions for Business, Education & Government since 1999

Site Search:

Subsystems

- Storage Area Network
- Direct Attached Storage
- Network Attached Storage
- High Availability Storage
- Open-E Storage Software

SAS

- SAS Adapters
- SAS Cables - External
- SAS Cables - Internal
- SAS Cables - Im to Ext
- SAS Enclosures & Cages
- SAS Expanders
- SAS Hard Drives
- SAS Host Bus Adapters
- SAS RAID Controllers

SATA

- SATA Cables & Adapters
- SATA Enclosures
- SATA Hard Drives
- SATA Solid State Drives
- SATA Hotswap Backplanes
- SATA Port Multiplier

Servers

- Rackmount Servers
- Rackmount Cases

SOBI

- Adapters, Cables, Controllers
- Enclosures, Hard Drives

Other Enclosures


- USB / Firewire
- Disk Duplexer Towers

Cart

View Cart






Login

1m SFF-8087 to SFF-8088 SAS Cable




\$59.50
Add to Cart

Part #: SAS-8887-1M

Specifications

Part #	SAS-8887-1M
Type	SATA / SAS cable
Connector	SFF-8087 (internal miniSAS, 36 pin miniSAS)
Connector	SFF-8088 (external miniSAS, 26 pin miniSAS)
Length	1 meter (~ 3.3 feet)
Used For...	Connect internal controller ports to an external enclosure without internal-to-external adapters.
See Also...	<p>Do you need a longer cable? 2 meter SFF-8087 to SFF-8088</p> <p>Do you need an adapter instead? SFF-8087 to SFF-8088 Adapters</p>




THE STORAGE SPECIALISTS


Do you still have questions?

Get answers right away, your way.
Free Phone, Fast Email, Live Chat.

5-Star Support ★★★★★

1-800-298-4173





We've been selling computer storage online since 1999 and have built a loyal following of Fortune 500 companies, educational institutions, government agencies, multimedia studios, consultants, you name it.

Our mission is to be competitive on selection and prices, while providing truly unmatched personal service. Everyone you reach here has in-depth experience with RAID storage. This means we can provide real-world insight into topics like performance, compatibility, bang for the buck, and the best solution for your needs.

Call 1-800-298-4173, email sales@pc-pitstop.com, or click the [live chat](#) button for help.

"The best customer service I have experienced from an online store. Emails answered within hours and an actual phone number that a human answers." read more

www.pc-pitstop.com/sas_cables_adapters/8887-1M.asp
1/2